# SAFETY DATA SHEET

#### 1. Identification

**Product number** 1000008332

**Product identifier** 19 OZ WINDOW KLEEN LB 12PK

10-01-2014 **Revision date** 

MAINT SUPPLY & MARKETING **Company information** 1101 E FRANCISCO BLVD.

SAN RAFEAL, CA 94901 United States

General Assistance Company phone **Emergency telephone US** 1-866-836-8855 1-952-852-4646 **Emergency telephone outside** 

Version # 02

09-24-2014 Supersedes date Recommended use Glass Cleaner Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Specific target organ toxicity, single exposure Category 1 **Health hazards** 

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Causes damage to organs.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this

If exposed: Call a poison center/doctor. Specific treatment (see this label). Response

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Not available. Hazard(s) not otherwise None known.

classified (HNOC)

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Methanol		67-56-1	2.5 - 10
Ethyl Alcohol		64-17-5	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below repo	rtable levels		90 - 100

Product name: 19 OZ WINDOW KLEEN LB 12PK

SDS US 1 / 11 \*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Do not use Inhalation

> mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Call a physician or Poison Control Center immediately.

Call a physician or Poison Control Center immediately. Eye contact Ingestion Rinse mouth. Get medical attention if symptoms occur.

Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and delayed

Skin contact

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. medical attention and special Symptoms may be delayed.

treatment needed **General information** 

Immediate medical attention is required. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Not available. Suitable extinguishing media

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

**Environmental precautions** 

Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Will ignite if exposed to intensive heat or open air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Do not get this material in contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep container dry. Refrigeration recommended. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
<b>US. ACGIH Threshold Limit Values</b>			
Components	Type	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Type	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
. ,		1000 ppm	
logical limit values		• •	

## Biological limit values

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)

Skin designation applies.

Product name: 19 OZ WINDOW KLEEN LB 12PK

SDS US

US - Tennesse OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear tight-fitting goggles or face shield. **Hand protection** Wear appropriate chemical resistant gloves.

Skin protection

Other Use of an impervious apron is recommended.

Skin protection

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Do not get in eyes. When using do not smoke. Do not get this material in contact with skin. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 23.01 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

**Viscosity** Not available.

Other information

Specific gravity 0.968 estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** 

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Exposure to air. Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact

with incompatible materials.

Oxygen. Do not mix with other chemicals. Incompatible materials

Risk of ignition.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

May cause damage to organs by inhalation. Prolonged inhalation may be harmful. Inhalation

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation. Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

#### Information on toxicological effects

# **Acute toxicity**

Product	Species	Test Results			
19 OZ WINDOW KLEEN LB 12PK (CAS Mixture)					
Acute					
Dermal					
LD50	Guinea pig	30568.8457 ml/kg, 24 Hours estimated			
		970.2286 ml/kg, 4 Days estimated			
	Rabbit	49755.8828 mg/kg estimated			
		2824.3066 ml/kg, 24 Hours estimated			
	Rat	22114 mg/kg			
Inhalation					
LC100	Cat	1800.036 % estimated			
LC50	Cat	2996.8423 mg/l, 4.5 Hours estimated			
		1532.6316 mg/l, 6 Hours estimated			
	Mouse	24740.4941 mg/l, 120 Minutes estimated			
		3427.9429 mg/l, 4 Hours estimated			
		3340.0469 mg/l, 24 Hours estimated			
		2787.0176 mg/l, 134 Minutes estimated			
		1040.0208 %, 120 Minutes estimated			
		320.0064 mm/l, 2 Hours estimated			
	Rabbit	53163.2109 ppm, 7 Hours estimated			
	Rat	48639.8242 ppm, 4 Hours estimated			
		4498.2456 mg/l, 4 Hours estimated			
		3073.6843 mg/l, 6 Hours estimated			
		204 mg/l/4h			

Product name: 19 OZ WINDOW KLEEN LB 12PK

SDS US

Product	Species	Test Results
Oral	D. H. Y	00074 0704 // // //
LD100	Rabbit	92371.0781 mg/kg estimated
LD50	Dog	92371.0781 mg/kg estimated
	Rat	25019.3789 mg/kg estimated
<i>Other</i> LD50	Mouse	96942 7656 malka estimated
	Mouse	86843.7656 mg/kg estimated  Test Results
Components Butane (CAS 106-97-8)	Species	rest Results
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		3
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	7800 ml/kg
		7060 mg/kg
Other		
LD50	Mouse	6000 mg/kg
	Rat	4070 mg/kg
Methanol (CAS 67-56-1)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		82.1 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Rat	1187 - 2769 mg/kg
Other		2222 #
LD50	Mouse	6000 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes
2000	Mode	52 %, 120 Minutes
		32 /0, 120 IVIIIIules

**Test Results** Components **Species** 1355 mg/l Rat

658 mg/l/4h

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Risk of cancer cannot be excluded with prolonged exposure. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Causes damage to organs.

Specific target organ toxicity -

repeated exposure

Respiratory system. Skin. Central nervous system. Eyes. Gastrointestinal tract.

Not likely, due to the form of the product. **Aspiration hazard** 

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects** 

**Further information** Danger of very serious irreversible effects.

# 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
19 OZ WINDOW KLEEN LB 12PK (CAS Mixture)				
Aquatic				
Algae	IC50	Algae	5714 mg/L, 72 Hours	
Fish	LC50	Fish	57589 mg/L, 96 Hours	
Components		Species	Test Results	
Ethyl Alcohol (CAS 64	<b>1</b> -17-5)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours	
Methanol (CAS 67-56	i-1)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

**Bioaccumulative potential** No data available. Partition coefficient n-octanol / water (log Kow)

2.89 Butane Ethyl Alcohol -0.31 Methanol -0.77Propane 2.36

Mobility in soil No data available.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. **Disposal instructions** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

#### US RCRA Hazardous Waste U List: Reference

Methanol (CAS 67-56-1) U154

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

# 14. Transport information

DOT

UN1950 **UN number** 

UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions 306 Packaging exceptions None Packaging non bulk Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

**UN** number UN1950

Aerosols, flammable **UN proper shipping name** 

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only **Packaging Exceptions** LTD QTY

**IMDG** 

UN1950 **UN number UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s)

Packing group

Not applicable.

**Environmental hazards** 

Marine pollutant No. **EmS** F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

LTD QTY

DOT



IATA; IMDG



# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations** 

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Methanol (CAS 67-56-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	2.5 - 10
1,4-Dioxane	123-91-1	0.01 - 0.1

 Chemical name
 CAS number
 % by wt.

 Safrole
 94-59-7
 0.01 - 0.1

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause birth

defects or other reproductive harm.

#### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

## US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Butane (CAS 106-97-8) Methanol (CAS 67-56-1) Propane (CAS 74-98-6)

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1) Listed: January 1, 1988 Safrole (CAS 94-59-7) Listed: January 1, 1988

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

# 16. Other information, including date of preparation or last revision

 Issue date
 09-24-2014

 Revision date
 10-01-2014

Version # 02

country(s).

**Disclaimer** We cannot anticipate all conditions under which this information and its product, or the products of

other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its

publication. The information given is designed only as a guidance for safe handling, use,

processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

**Revision Information** Product and Company Identification: Product and Company Identification