

## ***SAFETY DATA SHEET***

---

COMPANY IDENTITY: BRADY INDUSTRIES, LLC

SDS DATE: 10/26/2016

PRODUCT IDENTITY: SOLVENT SPOTTER

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH CFR 1910.1200 (HAZARD COMMUNICATIONS STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

PRODUCT IDENTITY: SOLVENT SPOTTER

SDS NUMBER: CR6486

COMPANY IDENTITY: BRADY INDUSTRIES, LLC

COMPANY ADDRESS: 7055 LINDELL ROAD LAS VEGAS, NV 89118

COMPANY PHONE: 1-800-293-4698

EMERGENCY PHONES: CHEMTEL: 1-800-255-3924

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **HAZARD STATEMENTS:**

**H100s = General, H200s = Physical, H300 = Health, H400s = Environmental**

H304 May be fatal if swallowed and enters airways.

#### **PRECAUTIONARY STATEMENTS:**

**P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.

P331 Do NOT induce vomiting.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do – Continue rinsing.

P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.

P405+102 Store locked up. Keep out of reach of children.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **MATERIAL**

#### **CAS#**

Distillates (petroleum), hydrotreated light 64742-47-8

Trace components: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant Additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

## SECTION 4. FIRST AID MEASURES

### EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. Roll eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

### SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

### INHALATION:

Move person to fresh air, if effects occur, consult a physician.

### SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

### NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

Victims of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take a copy of the label and SDS to physician or health professional with victim.

## SECTION 5. FIRE FIGHTING MEASURES

### FIRE & EXPLOSIONS PREVENTIVE MEASURES:

Isolate from extreme heat and open flame.

### EXTINGUISHING MEDIA:

Water, Water spray, foam, carbon dioxide (CO<sub>2</sub>). Dry powder.

### FLAMMABLE PROPERTIES:

NFPA Class IIIB combustible liquid.

FLASH POINT: 109°C, 229°F, ASTM D 93;

AUTOIGNITION TEMPERATURE: 216°C, 421°F ASTM E 659;.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel.

### PERSONAL PRECAUTIONS:

Spilled material may cause a slipping hazard. Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment.

### ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container, keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

### CONTAINMENT AND CLEAN-UP MEASURES:

Absorb spilled liquid with poly pads or other suitable absorbent materials. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. Dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13- Disposal Considerations).

## SECTION 7. HANDLING AND STORAGE

### HANDLING:

Product shipped/handled hot can cause thermal burns. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE:

Freezing will affect the physical condition and may damage the material. Keep in a dry cool place (0-30°C). Keep away from heat and sources of ignition.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)	
Water	7732-18-15	231-791-2	None Known	None Known	
Distillates Petroleum	64742-47-8	-----	None Known	None Known	
MATERIAL	CAS#	EIENECS#	CEILING	STEL (OSHA/ACGIH)	HAP
Distillates Petroleum	64742-47-8	-----	-----	None Known	No

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

#### RESPIRATORY EXPOSURE CONTROLS:

A respiratory protective program that meets OSHA CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

#### VENTILATION:

LOCAL EXHAUST: Necessary      MECHANICAL (General): Necessary

SPECIAL: None      OTHER: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

#### PERSONAL PROTECTION:

Wear OSHA Standard full face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

#### WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers. Wash at the end of each work shift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

### SECTION 9. PHYSICAL & CHEMICAL PROPERTIES:

APPEARANCE:	Water white/straw yellow liquid
ODOR:	Hydrocarbons
ODOR THRESHOLD:	Not Available
Ph (Neutrality):	N/A
MELTING POINT/FREEZING POINT:	<68°C, <90°F, ASTM D 2386
BOILING RANGE (IBP, 50%, Dry Point):	Not Applicable
FLASH POINT (TEST METHOD):	109°C/229°F ASTM D 93
EVAPORATION RATE (n-BUTYL ACETATE=1):	N/A
FLAMMABILITY CLASSIFICATION:	Combustible
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	0.5% (v)
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	7.0 % (v)
VAPOR PRESSURE (mm of Hg)@20 C:	0.02
VAPOR DENSITY (air = 1):	6.7
GRAVITY @ 68/68F / 20/20C:	
SPECIFIC GRAVITY (Water = 1):	no data available
DENSITY:	0.821 g/cm <sup>3</sup> @ 15.5 °C
WATER SOLUBILITY:	Negligible
VISCOSITY (mPa.s):	N/A
AUTO IGNITION TEMPERATURE:	216°C, 421°F, ASTM E 659
DECOMPOSITION TEMPERAURE:	Not Available

## SECTION 10. STABILITY & REACTIVITY

### STABILITY:

Stable under most conditions.

### CONDITIONS TO AVOID:

Isolate from extreme heat, and open flame.

### MATERIALS TO AVOID:

Oxidizing agents may cause exothermic reactions.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Hazardous gases and vapors produced in fire are oxides of carbon.

### HAZARDOUS POLYMERIZATION:

None.

## SECTION 11. TOXICOLOGICAL INFORMATION

**Additional Remarks**      The product itself has not been tested.

**LD50 Oral:**      LD50/oral/rat > 5000 mg/kg (estimated)

**LD50 Dermal**      2,000-4,000 mg/kg (Rabbit).

**LC50 Inhalation** (4 hours) (Rat) > 0.5 mg/l. All rats survived at indicated concentrations.

### Reproductive toxicity

No data available.

## SECTION 12. ECOLOGICAL INFORMATION

### AQUATIC TOXICITY:

Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility.

### FRESH FISH TOXICITY:

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

Processing, use or contamination may change the waste management options. Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

**SECTION 14. TRANSPORT INFORMATION**

**UN/NA:** N/A

**Classification:** NON D.O.T REGULATED

**Proper Shipping Name:** LIQUID NON REGULATED

**D.O.T Hazard Name (49CFR 172.101):** NONE

**D.O.T. ID Number (49CFR 172.101):** NONE

**D.O.T. Hazard Class (49CFR 172.101):** NONE

**RCRA Hazard Class (40cfr261) (If discarded):** NONE

**E.P.A. Priority pollutants (40CFR 122.53):** NONE

**HAZARD RATINGS:**

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 1, PHYSICAL HAZARD: 0

(Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating system.

### **NOTICE**

All information, recommendations, and suggestions appearing herein concerning this product are based upon data obtained from the manufacturer and/or recognized technical sources; however, BRADY INDUSTRIES, LLC makes no warranty, representation or guaranty as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of the product. Additional product literature may be available upon request. Since actual use by others is beyond our control, no warranty, express or implied is made by BRADY INDUSTRIES, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of the product nor does BRADY INDUSTRIES, LLC assume any liability arising out of use by others of this product.