

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 16-Nov-2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: CAUSTIC CLEANER FP

Product Number: 3189

Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 1 Sub-category A

Serious Eye Damage/Eye Irritation: Category 1 Corrosive to Metals: Category 1

GHS Label Elements

Signal Word: Danger

Symbols:

Response:

Hazard Statements: Causes severe skin burns and serious eye damage.

May be corrosive to metals.

Precautionary Statements:

Prevention: Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Keep in original or other corrosion resistant container.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

-Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Spill: Absorb spillage to prevent material damage.

Storage: Store locked up. Store in corrosion resistant container.

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: • Corrosive

Harmful or fatal if swallowed.

· Harmful contact may not cause immediate pain.

• Inhalation of vapors or mist may cause respiratory irritation or damage.

• Take off and destroy contaminated shoes.

· Keep out of reach of children

• NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	40-70
Sodium Hydroxide	1310-73-2	15-40
Sodium Silicate	1344-09-8	1-5
Sodium Gluceptate	31138-65-5	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Skin Contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse. Discard or destroy contaminated shoes.

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the

Chemical:

Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

Precautions for Firefighters: protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Environmental Precautions: Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with Methods for Clean-Up:

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach **Storage Conditions:**

of children. Keep from freezing.

Suggested Shelf Life: Minimum of 2 years from date of manufacture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Sodium Hydroxide	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³	IDLH: 10 mg/m ³
1310-73-2		(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Engineering Controls: Provide good general ventilation.

> If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. **Skin and Body Protection:** Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other

protective equipment should be considered in order to prevent or minimize contact with this

product.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

Wash hands and any exposed skin thoroughly after handling. **General Hygiene Considerations:**

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid	
Color:	Dark brown	
Odor:	Pungent	
pH:	14	
Melting Point / Freezing Point:	No information available	
Boiling Point / Boiling Range:	124 °C / 255 °F	
Flash Point:	> 124 °C / > 255 °F ASTM D56	
Evaporation Rate:	< 1	
Flammability (solid, gas)	No information available	
Upper Flammability Limit:	No information available	
Lower Flammability Limit:	No information available	
Vapor Pressure:	No information available	
Vapor Density:	No information available	
Specific Gravity:	1.4-1.5	
Solubility(ies):	Soluble in water	
Partition Coefficient:	No information available	
Autoignition Temperature:	No information available	
Decomposition Temperature:	No information available	
Viscosity:	No information available	

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Contact with aluminum or other reactive metals may release hydrogen gas.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition Strong oxidizing agents. Strong acids.

May include carbon monoxide, carbon diox

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact: Pain, redness, blistering and possible chemical burn.

-Inhalation: Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

coughing.

-Ingestion: Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: -Eyes. Respiratory System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 77872 mg/kg ATEmix (dermal): 3809 mg/kg

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	Not Available	Not Available
7732-18-5			
Sodium Hydroxide Not Available		= 1350 mg/kg (Rabbit)	Not Available

1310-73-2			
Sodium Silicate	= 1960 mg/kg (Rat)	Not Available	Not Available
1344-09-8			

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Sodium Hydroxide 1310-73-2	Not Available	45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	Not Available
Sodium Silicate 1344-09-8	Not Available	301 - 478: 96 h Lepomis macrochirus mg/L LC50 3185: 96 h Brachydanio rerio	Not Available	Not Available
		mg/L LC50 semi-static		

Persistence and Degradability:
Bioaccumulation:No information available.
No information available.Other Adverse Effects:No information available

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:

Contaminated Packaging:

Dispose of in accordance with federal, state and local regulations.

Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number: D002

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class: 8
Packing Group: ||

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size,

and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s.,(contains sodium hydroxide)

Hazard Class: 8
Packing Group: |

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard: Yes Chronic Health Hazard: No

Fire Hazard: No

Fire Hazard: No
Sudden release of pressure hazard: No
Reactive Hazard: No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 0 Instability: 1 Special: N/A

HMIS Health Hazards: 3 Flammability: 0 Physical Hazards: 1

Revision Date: 16-Nov-2021

Reasons for Revision: No information available

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet