

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 25-Nov-2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: CARPET STAIN REMOVER

Product Number: 6374

Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Serious Eye Damage/Eye Irritation: Category 2A
Flammable Aerosols Category 1
Gases Under Pressure Liquefied gas

GHS Label Elements

Signal Word: Danger

Symbols:

I W

Hazard Statements: Causes serious eye irritation

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated

Precautionary Statements:

Prevention: Wash hands and any exposed skin thoroughly after handling.

Wear eye / face protection

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal

Response:

-EyesIF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C) Store in a

well-ventilated place

Hazards Not Otherwise Classified: Not Applicable

Other Information: • May be harmful if swallowed.

· May cause skin irritation.

Not Applicable

• Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	60-100
Butoxyethanol	111-76-2	5-10
Isopropyl Alcohol	67-63-0	1-5
Propane	74-98-6	1-5
Butane	106-97-8	1-5
Sodium Lauryl Sulfate	73296-89-6	0.1-1
Ammonium Hydroxide	1336-21-6	0.1-1
Sodium Nitrite	7632-00-0	0.1-1
Dimethicone	63148-62-9	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash with soap and water. If skin irritation occurs: Get medical attention.

-Skin Contact: Wash with soap and water. If skin irritation occurs: Get medical attention.
-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison control center or physician if you feel unwell.

-Ingestion: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention if you feel unwell.

Note to Physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Wa

Specific Hazards Arising from the

Chemical:

Disposal:

Water spray (fog), Foam

Extremely flammable aerosol. Exposure to high temperature may cause containers to burst.

Bursting aerosol containers may be propelled from fire at high speed.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters:

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. In the event of fire

and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Intentional misuse

by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after

handling.

Storage Conditions: NFPA 30B Level 1 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°.

Exposure to high temperature may cause containers to burst. Keep out of the reach of

children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection: Wear splash goggles.

Skin and Body Protection:

Respiratory Protection:

Not required with expected use.

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 25-Nov-2019

Appearance/Physical State:	Aerosol
Color:	White
Odor:	solvent
pH:	10.0-11.0
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	100 °C / 212 °F (Product without propellant)
Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)
Evaporation Rate:	<1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	0.96 (Product without propellant)
Solubility(ies):	No information available.
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition May include carbon monoxide, carbon d

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and blurred vision.

-Skin Contact: Drying of the skin.

-Inhalation: Nasal discomfort and coughing.-Ingestion: Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: -Eyes. Respiratory System. -Skin. Blood. Central nervous system. hematopoietic system.

kidney. Liver.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):

ATEmix (dermal):

ATEmix (inhalation-gas):

ATEmix (inhalation-dust/mist):

ATEmix (inhalation-vapor):

4417 mg/kg
10809 mg/kg
10511385
15.7 mg/l
22.9 mg/l

Component Acute Toxicity Information

	Component Acute Toxicity information				
	Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Water 7732-18-5		> 90 mL/kg (Rat)	Not Available	Not Available	
	Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h	

Isopropyl Alcohol 67-63-0	= 1870 mg/kg(Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³ (Rat) 4 h
Propane 74-98-6	Not Available	Not Available	= 658 mg/L (Rat) 4 h
Butane 106-97-8	Not Available	Not Available	= 658 g/m ³ (Rat) 4 h
Sodium Lauryl Sulfate 73296-89-6	= 1783 mg/kg (Rat)	Not Available	Not Available
Ammonium Hydroxide 1336-21-6	= 350 mg/kg (Rat)	Not Available	Not Available
Sodium Nitrite 7632-00-0	= 85 mg/kg(Rat)	Not Available	= 5.5 mg/L (Rat) 4 h
Dimethicone 63148-62-9	> 24 g/kg (Rat)	Not Available	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1000: 48 h Daphnia magna mg/L EC50
Isopropyl Alcohol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	Not Available	13299: 48 h Daphnia magna mg/L EC50
Sodium Lauryl Sulfate 73296-89-6	42: 96 h Desmodesmus subspicatus mg/L EC50	Not Available	Not Available	Not Available
Ammonium Hydroxide 1336-21-6	Not Available	8.2: 96 h Pimephales promelas mg/L LC50	Not Available	0.66: 48 h water flea mg/L EC50 0.66: 48 h Daphnia pulex mg/L EC50
Sodium Nitrite 7632-00-0	Not Available	0.19: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.092 - 0.13: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.4 - 0.6: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.65 - 1: 96 h Oncorhynchus mykiss mg/L LC50 static 2.3: 96 h Pimephales promelas mg/L LC50 flow-through 20: 96 h Pimephales promelas mg/L LC50 static	Not Available	Not Available

Persistence and Degradability:
Bioaccumulation:No information available.
No information available.Other Adverse Effects:No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with

federal, state and local regulations.

6374 - CARPET STAIN REMOVER Revision Date: 25-Nov-2019

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1950
Proper Shipping Name: Aerosols
Hazard Class: 2.1

Special Provisions: This product meets the exception requirements of section 49 CFR 173.306 as a limited

quantity and may be shipped as a limited quantity.

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN1950
Proper Shipping Name: Aerosols
Hazard Class: 2.1

Additional information: Limited Quantity

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

Butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or SulfonateChemical Category N230

SARA 311/312 Hazard Categories

Acute Health Hazard:

Chronic Health Hazard:

No
Fire Hazard:

Sudden release of pressure hazard:

Reactive Hazard:

No
No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 2 Flammability: 1 Instability: 0 Special: N/A

HMIS Health Hazards: 2 Flammability: 2 Physical Hazards: 2

Revision Date: 25-Nov-2019

Reasons for Revision: Section, 2, 3, 11, and, 12

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet