



Safety Data Sheet

Spartan Chemical Company, Inc.

Revision Date: 13-May-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: AQUASPORT 2-PART WOOD FLOOR FINISH PART A
Product Number: 5832 , 5835, 583400, 583104
Recommended Use: Floor Finish
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 2A
Reproductive Toxicity: Category 1B
Specific Target Organ Toxicity (Single Exposure): Category 3

GHS Label Elements

Signal Word:

Symbols:

Danger



Hazard Statements:

Causes skin irritation.
Causes serious eye irritation
May damage fertility or the unborn child
May cause respiratory irritation

Precautionary Statements:

Prevention:

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear eye / face protection
Wear protective gloves
Use personal protective equipment as required
Wash hands and any exposed skin thoroughly after handling.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.

Response:

-Eyes

If exposed or concerned: Get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

-Skin	IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.
-Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	• May be harmful if swallowed. • Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	40-70
aliphatic urethane	PROPRIETARY	10-30
1-methyl-2-pyrrolidinone	872-50-4	3-7
styrene acrylic copolymer	PROPRIETARY	1-5
dipropylene glycol monomethyl ether	34590-94-8	1-5
2,5,8,11 tetramethyl 6 dodecyn-5,8 diol ethoxylate	169117-72-0	1-5
triethylamine	121-44-8	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Skin Contact:	Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical attention.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
-Ingestion:	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.
Note to Physicians:	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire
Specific Hazards Arising from the Chemical:	Dried product is capable of burning. Combustion products are toxic.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
dipropylene glycol monomethyl ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³
triethylamine 121-44-8	STEL: 3 ppm TWA: 1 ppm S*	TWA: 25 ppm TWA: 100 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 40 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 60 mg/m ³	IDLH: 200 ppm

Engineering Controls: Provide good general ventilation.
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection:

Wear rubber or other chemical-resistant gloves.

Respiratory Protection:

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.
See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	light brown
Odor:	Bland
pH:	7.5-8.5
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	102 °C / 216 °F
Flash Point:	> 102 °C / > 216 °F ASTM D56
Evaporation Rate:	<1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.048
Solubility(ies):	No information available.
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products:	May include carbon monoxide, carbon dioxide (CO ₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:	
-Eye Contact:	Pain, redness, swelling of the conjunctiva and blurred vision.
-Skin Contact:	Pain, redness and cracking of the skin.
-Inhalation:	Nasal discomfort and coughing.
-Ingestion:	Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effects	
Product Information:	Data not available or insufficient for classification.
Chronic Toxicity:	May cause adverse liver effects.
Target Organ Effects:	Central nervous system. Central Vascular System (CVS). -Eyes. kidney. Liver. Respiratory System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):	16233 mg/kg
ATEmix (dermal):	21347 mg/kg
ATEmix (inhalation-dust/mist):	28.9 mg/l
ATEmix (inhalation-vapor):	426.3 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available

1-methyl-2-pyrrolidinone 872-50-4	= 3598 mg/kg (Rat)	= 2500 mg/kg (Rat) > 5000 mg/kg (Rabbit)	= 3.1 mg/L (Rat) 4 h
dipropylene glycol monomethyl ether 34590-94-8	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	Not Available
triethylamine 121-44-8	= 460 mg/kg (Rat)	= 416 mg/kg (Rabbit) = 570 µL/kg (Rabbit)	= 0.42 mg/L (Rat) 1 h = 3496 ppm (Rat) 1 h

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
1-methyl-2-pyrrolidinone 872-50-4	500: 72 h Desmodesmus subspicatus mg/L EC50	832: 96 h Lepomis macrochirus mg/L LC50 static 4000: 96 h Leuciscus idus mg/L LC50 static 1072: 96 h Pimephales promelas mg/L LC50 static 1400: 96 h Poecilia reticulata mg/L LC50 static	Not Available	4897: 48 h Daphnia magna mg/L EC50
dipropylene glycol monomethyl ether 34590-94-8	Not Available	10000: 96 h Pimephales promelas mg/L LC50 static	Not Available	1919: 48 h Daphnia magna mg/L LC50
triethylamine 121-44-8	Not Available	43.7: 96 h Pimephales promelas mg/L LC50 static	Not Available	200: 48 h Daphnia magna mg/L EC50

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number: U404

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
triethylamine 121-44-8	U404	Included in waste streams: K156, K157		U404

14. TRANSPORT INFORMATION

DOT: Not Regulated

Proper Shipping Name: Non-Hazardous Product

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

1-methyl-2-pyrrolidinone

CAS No 872-50-4

triethylamine

CAS No 121-44-8

SARA 311/312 Hazard Categories

Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
1-methyl-2-pyrrolidinone - 872-50-4	Developmental
acrylonitrile - 107-13-1	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

16. OTHER INFORMATION

NFPA	Health Hazards: 2	Flammability: 0	Instability: 0	Special: N/A
HMIS	Health Hazards: 2*	Flammability: 0	Physical Hazards: 0	

Revision Date: 13-May-2015
Reasons for Revision: No information available.

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet