

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): Product Division: XTREME CLEAN CARGO Janitorial

Product Number: 2047

Spartan Chemical Company, Inc. Product/Technical 1-(800)-537-8990

Information:

1110 Spartan Drive Medical Emergency:1-(888)-314-6171 (24 hours)

Maumee OH 43537 Chemical Leak/SpilCHEMTREC 1-(800) 424-9300 (24

Emergency:hours)

Shipping Description: Cleaning compounds, liquid, n.o.s.				
NFPA Ratings:		HMIS Ratings:		
Health:	2 - Moderate	Health:	2 - Moderate	
Fire:	0 - Minimal	Fire:	0 - Minimal	
Reactivity:	0 - Minimal	Reactivity:	0 - Minimal	
		Pers. Prot. Equip.:	See Section VIII	

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z- 1 - A		NTP, IARC	
Chemical Name(s)	% W	CAS Registry No.	TWA mg/m ³	STEL mg/m ³	CELING mg/m ³	or OSHA Carcinogen
Tetrasodium EDTA	5-10	64-02-8	Not Established	Not Established	Not Established	No
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No
Phosphate ester	1-5	68130-47-2	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point:	212 °F	Vapor Pressure:	Not determined
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete
pH:	11.5- 12.0	Specific Gravity (H ₂ O=1):	
Evaporation Rate (but.ace.=1):		Percent Solid by Weight:	10-15
Physical State:	Liquid		
Appearance & Odor: Rose colored liquid, bland odor			

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	> 212°F	Method Used:	ASTM-D56
Flammable Limits: 1	Not Established	Flame Extension:	N/A
Extinguishing Media: Product does not support of for surrounding fire.		ombustion. Use extingui	ishing media appropriate
	Wear NIOSH approved sell clothing. Cool fire-exposed		
Unusual Fire & Explosive Hazards:	Combustion products are to	oxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes; Oral
Effects of Overexposure Conditions to Avoid	d: redness. Causes skin irritation: S May be harmful if swall nausea and diarrhea. Inhalation of product m may include coughing and Do not get in eyes, on ski	ymptoms may include pain, swelling and ymptoms may include pain, swelling and redness. owed: Symptoms may include abdominal pain, ist may cause respiratory irritation: Symptoms I difficulty breathing. in, or on clothing. Do not swallow. Avoid Wash thoroughly after handling.
	Use of this product may a disorders including asthm	ggravate preexisting skin; eye and respiratory a and dermatitis.

Emergency & First Aid Procedures:

Eyes:	Flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing. Flush skin with water for at least 15 minutes. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation or dizziness; move person to fresh air. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability:	Stable	Incompatible Materials:	Strong oxidizing agents
Hazardous Decomposition Products:		Hazardous Polymerization:	Will Not Occur

Steps to be Taken in Case	Small spills of one gallon or less may be flushed with plenty of water to
Material is Released or	sanitary sewer system (If permitted by local sewer regulations). Dike and
Spilled:	contain large spills with inert material and transfer liquid to containers for
	disposal. Keep spill out of storm sewers and waterways.
Waste Disposal Method:	Assure conformance with federal, state and local regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
	Rubber or other impervious gloves are recommended when handling undiluted product
Eye Protection(Specify Type):	Splash goggles are recommended when handling undiluted product
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	
Other Precautions:	Keep out of reach of children.

SCC 11/20/2006 Name: Ronald T. Cook Title: Manager, Regulatory Affairs

XTREME CLEAN CARGO Effective 11/20/2006

Date:

Ref: 29 CFR 1910.1200 Changes: New Product

(OSHA)

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.