

A390-20

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Misty Penetrating Lubricant
Product Number: A00390
Product Use: Penetrant / Lubricant.
Manufacturer/Supplier: Amrep, Inc.
990 Industrial Park Drive
Marietta, GA 30062
Phone Number: (770) 422-2071 (Mon - Fri / 8am - 5pm ET)
D.O.T. Emergency Phone: CHEM TEL (800) 255-3924
INTERNATIONAL: +01-813-248-0584
Date of Preparation: January 16, 2008 **Revision #:** 1.0

Section 2: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****HMIS:** See Section 15**WARNING**

TOXIC BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.
CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.
Skin: May cause skin irritation.
Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.
Inhalation: Toxic by inhalation. May cause respiratory tract irritation. May cause asphyxiation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Handling can cause dry skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredient | CAS # | Wt. % |
|--|--------------|--------------|
| Perchloroethylene | 127-18-4 | 30 - 60 |
| Stoddard solvent | 8052-41-3 | 10 - 30 |
| Trichloroethylene | 79-01-6 | 5 - 10 |
| Sulfonic acids, petroleum, calcium salts | 61789-86-4 | 1 - 5 |
| Carbon dioxide | 124-38-9 | 1 - 5 |

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, foam, carbon dioxide.

Unsuitable Extinguishing Media: Water.

Products of Combustion: May include, and are not limited to: oxides of carbon, oxides of sulfur, HCl, chlorine, small amounts of phosgene and hydrogen fluoride.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49°C / 120°F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| Ingredient | Exposure Limits | |
|--|-----------------|----------------|
| | OSHA-PEL | ACGIH-TLV |
| Perchloroethylene | 25 ppm | 25 ppm |
| Stoddard solvent | 100 ppm | 100 ppm |
| Trichloroethylene | 100 ppm | 50 ppm |
| Sulfonic acids, petroleum, calcium salts | Not available. | Not available. |
| Carbon dioxide | 5000 ppm | 5000 ppm |

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------|-------------------------|
| Appearance: | Opaque. |
| Color: | Brown. |
| Odour: | Solvent. |
| Odour Threshold: | Not available. |
| Physical State: | Gas/Pressurized Liquid. |
| pH: | Not applicable. |
| Viscosity: | Not available. |
| Freezing Point: | Not available. |
| Boiling Point: | Not available. |
| Flash Point: | Not available. |
| Evaporation Rate: | Not available. |

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

| | |
|--|-----------------------------------|
| Lower Flammability Limit: | Not available. |
| Upper Flammability Limit: | Not available. |
| Vapor Pressure: | Not available. |
| Vapor Density: | Not available. |
| Specific Gravity: | 1.210 (Liquid Concentrate) |
| Solubility in Water: | Insoluble. |
| Coefficient of Water/Oil Distribution: | Not available. |
| Auto-ignition Temperature: | Not available. |
| Percent Volatile, wt. %: | Not available. |
| VOC content, wt. %: | 27.9% (US federal/CARB/OTC/LADCO) |

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers. Aluminum. Magnesium. Contact with reactive metals.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon, oxides of sulfur, HCl, chlorine, small amounts of phosgene and hydrogen fluoride.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

| Ingredient | LD ₅₀ (oral) | LC ₅₀ |
|--|-------------------------|-----------------------------------|
| Perchloroethylene | 2629 mg/kg, rat | 34.2 g/m ³ 8hrs, rat |
| Stoddard solvent | > 5000 mg/kg, rat | > 5500 mg/m ³ 4hr, rat |
| Trichloroethylene | 5650 mg/kg, rat | Not available. |
| Sulfonic acids, petroleum, calcium salts | Not available. | Not available. |
| Carbon dioxide | Not available. | Not available. |

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Handling can cause dry skin.

Ingestion: Not a normal route of exposure. Harmful; may cause lung damage if swallowed.

Inhalation: Toxic by Inhalation. May cause respiratory tract irritation. May cause asphyxiation. This product may be aspirated into the lungs and cause chemical pneumonitis. Vapours may cause drowsiness and dizziness.

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: (Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spleen, lung or brain damage, cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously occurring malignant tumors in certain laboratory rats and mice.

Carcinogenicity: Hazardous by WHMIS/OSHA criteria.

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Perchloroethylene
Stoddard solvent
Trichloroethylene
Sulfonic acids, petroleum, calcium salts
Carbon dioxide

G-A3, I-2A, N-2, CP65
Not listed.
I-2A, N-2, CP65
Not listed.
Not listed.

* See Section 15 for more information.

Mutagenicity: Hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

TDG Classification

Limited Quantity

MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III

| Ingredient | Section 302 (EHS) TPQ (lbs.) | Section 304 EHS RQ (lbs.) | CERCLA RQ (lbs.) | Section 313 |
|---|------------------------------------|------------------------------|---------------------|----------------|
| Perchloroethylene | Not listed. | Not listed. | 100 | 313 |
| Stoddard solvent | Not listed. | Not listed. | Not listed. | Not listed. |
| Trichloroethylene | Not listed. | Not listed. | 100 | 313 |
| Sulfonic acids, petroleum, calcium salts | Not listed. | Not listed. | Not listed. | Not listed. |
| Carbon dioxide | Not listed. | Not listed. | Not listed. | Not listed. |

State Regulations

California Proposition 65:

This product contains chemicals known to the state of California to cause cancer.

Global Inventories

| Ingredient | Canada DSL/NDSL | USA TSCA |
|--|--------------------|-------------|
| Perchloroethylene | DSL | Yes. |
| Stoddard solvent | DSL | Yes. |
| Trichloroethylene | DSL | Yes. |
| Sulfonic acids, petroleum, calcium salts | DSL | Yes. |
| Carbon dioxide | DSL | Yes. |

HMIS - Hazardous Materials Identification System

Health - 2 Flammability - 0 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class A - Compressed Gas
Class D1B - Toxic Material
Class D2A - Carcinogenicity
Class D2B - Mutagenicity
Class D2B - Chronic Toxic Effects
Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



MATERIAL SAFETY DATA SHEET

Misty Penetrating Lubricant

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: January 16, 2011

Prepared by: Nexreg Compliance Inc.

Prepared for: Amrep, Inc.

Phone: (770) 422-2071 (Mon - Fri / 8am - 5pm ET)