

# **Material Safety Data Sheet**

# This MSDS is prepared in accordance with OSHA 1910.1200, Canadian WHMIS, and ANSI.

Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
Class D-2B: Material causing other toxic effects (TOXIC).

HCS Class: Irritating substance, HCS Class: Combustible liquid IIIA having a flash point between 60.0°C (140°F) and 93.3°C (200°F).

WHMIS (Pictograms)

WHMIS (Classification)

**HCS** 

Section 1. Che	emical Rroduct and Company Identification		
Product Name/ Trade name	XL Catalyst	Code	B0662
	Not available.	CAS#	Mixture.
Synonym Chemical Family	Not available.	Validation Date	10/21/2008
Chemical Formula	Not applicable.	Print Date	10/21/2008
Manufacturer/ Supplier		In Case of CHI Emergency	EMTREC (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	<b>3</b> 4	tective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC <sub>50</sub> /LD <sub>51</sub>
Polyfunctional Azirldine 2-Propoxyethanol	64265-57-2 2807-30-9	50 - 100 10 - 25	Not available. ACGIH TLV (United States). Skin TWA: 25 ppm 8 hour(s).	Not available. Not available.

Section 3. Hazards Identification			
Potential Acute Health May cause severe eye irritation. Skin irritation. May cause skin sensitizat swallowed, Irritating to mouth, throat and stomach.			
Potential Chronic Health Effects	Severely irritating to the eyes. May aggravate existing skin conditions. May cause sensitization by skin contact. May aggravate existing respiratory conditions. May cause sensitization by inhalation.		
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH. Mutagenic in test systems.		

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.	
Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse Thoroughly clean shoes before reuse. Get medical attention.	
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.	

Section 5. Fire Fighting Measures		
Products of Combustion	Not available.	
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water , fog or foam. Do not use water jet.	
Special Remarks on Fire Hazards	Not available.	
Special Remarks on Explosion Hazards	Not available.	

į

Section 6. Accidental Release Measures			
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.		
Large Spill and Leak	Absorb with DRY earth, sand or other non-combustible material. Do not allow any potentially contaminated water including rain water, runoff from fire fighting or spills to enter any waterway, sewer or drain.		
Personal Protection in Case of a Large Spill	Splash goggles. Gloves. Light protective clothing. Boots. Wear appropriate respirator when ventilation is inadequate.		

Section 7. Handling and Storage			
Precautions	Keep away from heat. Do not breathe gas/fumes/ vapor/spray. Do not ingest. If ingested, seek medical advice immediately and show the container or the label.		
Incompatibility	alkalis oxidizing agents		
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.		

Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection Eye	ສ Safety glasses.
Вос	by No special protective clothing is required.
Respirator	y A respirator is not needed under normal and intended conditions of product use.
Hana	Impervious gloves.
Protective Clothing (Pictograms)	
Exposure Limits	See Section 2 For Applicable Exposure Limits

Section 9. Physic	al and Chemical Proper	ties	
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	Not available.
рН	Not available.	Color	White.
Boiling/Condensation Point	The lowest known value is 10	0°C (212°F) (Water).	
Melting/Freezing Point	May start to solidify at 0°C (32°F) based on data for: Water.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.0272 (Water = 1)		

Vapor Pressure	Not available.
Vapor Density	>1 (Air = 1)
Volatility	Not available.
VOC	271 (g/l).
Evaporation Rate	<1 compared to Butyl acetate.
Dispersion Properties	See solubility in water.
Solubility	Miscible in water.
The Product is:	May be combustible at high temperature.
Auto-ignition Temperature	Not available.
Flash Points	Closed cup: >176.67°C (350°F). (Setaflash.)
Flammable Limits	Not available.
Fire Hazards in Presence of Various Substances	Not available.
Explosion Hazards in Presence of Various Substances	Not available.

Section 10. Stability and Reactivity Data		
Stability	The product is stable.	
Incompatibility with Various Substances	alkalis oxidizing agents	, ,
Hazardous Decompositi	ion Not available.	

Section 11. Toxic	ological Information
Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	LD50: Not available. LC50: Not available.
Acute Effects on Humans	
Eye	s Irritating to eyes.
Ski	r Irritation of the product in case of skin contact: Not available. Sensitization of the product: Not available.
Inhalatio	May cause, headache, dizziness, and nausea
Ingestion	n nausea, Vomiting
Chronic Effects on Humans	May aggravate existing respiratory conditions.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

Section 12. Ecolo	gical Information	
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	Not available.	
Toxicity of the Products of Biodegradation	f Not available.	
Special Remarks on the Products of Biodegradation	Not available.	

# Section 14. Transport Information DOT (U.S.A) (Pictograms) TDG Classification - Not a TDG controlled material. PIN UN, Proper Shipping Not applicable. Name, PG Maritime Transportation Not available. Special Provisions for Not available.

WHMIS (Classification)	Class D-28: Material causing other (oxid effects (TOXIC).  No products were found.				
Regulatory Lists					
Other Regulations	Not available, or of its ingredients				
Other Classifications	HCS (U.S.A.)	HCS Class: irritating substance.			
	USA Regulatory Lists	a to the product of the state of			

Transport

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: N-Methyl-2-Pyrrolidone SARA 313 toxic chemical notification and release reporting: N-Methyl-2-Pyrrolidone 6.6% DSD (EEC) This product is not classified according to the EU regulations. International No products were found. Regulations Lists Hazardous Material 1 National Fire Information System Flammability Protection Flammability (U.S.A.) Association Health ( Instability Physical Hazard (U.S.A.) The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product. Specific Hazard

## Section 16. Other Information

Validated by LMorsch on 8/20/2008.

Verified by LMorsch. Printed 8/20/2008.

Information Contact Basic Coatings

1001 Brown Avenue Toledo, Ohio (800) 247-5471

## Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sala responsibility of the user. All materials may present unknown hazards and should be used with

caution. Although certain hazards are described herein, we connot guarantee that these are the only hazards that exist.

Validated on 8/20/2008.

Hydroline Plus Gloss

Page: 5/5

## Continued on Next Page