CG0105; CG0603 Brady Industries, HQ

MSDS

Material Safety Data Sheet 4056

Conforms to ANSI Z-400.1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

Las Vegas, NV 89188 (800) 293-4698

1 Chemical Product and Company Identification

Product: Oven & Grill Cleaner Classification: Specialty E20

2 Composition/Information on Hazardous Ingredients						
	CAS#	%	OSHA(PEL)	TLV(ppm)	Other	
Material 2- Butoxyethanol*	111-76-2	<5	25 ppm	25 ppm	OSHA-50	
Sodium Metasilicate	1344-09-8	<2	N/A	N/A	N/A	
	1310-73-2	<7	N/A	2 mg/m³	N/A	
Sodium Hydroxide	1010102					

3 Hazards Identification

Emergency Overview: Irritant. Causes skin irritation and eye damage. Avoid contact with skin and eyes.

DANGER

Contact with Eyes: This product is destructive to eye tissues. Will cause burns that result in damage to the eyes and

even blindness if the solution remains in contact with the eye for a prolonged period.

Contact with Skin: Repeated or prolonged contact with skin may cause irritation, drying and/or dermatitis.

Skin Absorption: A single prolonged exposure may result in absorption of toxic amounts.

Ingestion Symptoms: Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Airborne concentrations of mist/vapor may cause damage to the upper respiratory tract and even

lung tissue. If the product is heated, vapors are acutely toxic.

Chronic Effects: Respiratory tract damage may result in increased succeptability to respiratory illness. Excessive

inhalation exposure may result in liver and kidney injury.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

	Oven & Grill Cleaner Page 1 of 3
1/5/2010 0001 4056	Over a dill cleaner i ago i or o
1 1/3/2010 1 0001 4000	

5 Fire Fighting Measures

Flash Point(F° TCC): >210°F

Flammable Limits: LEL No Data

UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

None

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

1/5/2010	i 0001 l	1 4056

9 Physical and Ch	: D				
	emicai Propert	ies			
Boiling Point(F°):	>212°F	Solubility in Water:	Soluble	Odor:	Butyl
Specific Gravity:	1.09	Volatiles(% by Wt.):	89	pH:	13 - 14
Appearance:	Yellow	Vapor Density:	>1	VOC:	<100 g/L
Evaporation Rate:	<1	Vapor Pressure:	<17 mm Hg	Freezing Point(F°):	<32°F
		< means less than	> means greater tha		
These p Typical v	ihysical data are alues should no	typical values based on mat t be construed as a guarante	terial tested but may eed analysis of any sp	vary from sample to sal pecific lot or as specific	items.
10 Stability and Re	eactivity				
Stability: Stable	Co	nditions to Avoid: Heat			
Materials to Avoid	: Strong Oxidiz	ers			
Hazardous Decon	nposition Prod	ucts:			
Oxides of carbon	and nitrogen				
Hazardous Polyme Will Not Occur	erization:				
11 Toxicological I					
No Toxicology Infor		0lę.			
12 Ecological Info	rmation				
No data available.					
· · · · · · · · · · · · · · · · · · ·		 -			····
13 Disposal Consi	derations				
13 Disposal Consi Waste Disposal M	ethod:	with federal, state and local	regulations		
13 Disposal Consi Waste Disposal M	ethod: in accordance	with federal, state and local	regulations		
13 Disposal Consi Waste Disposal M Dispose of waste	ethod: e in accordance mation	with federal, state and local r	regulations ID Number: UN176	0 Hazard Class	s : 8
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor	ethod: e in accordance mation Hazard	Code: 1122		0 Hazard Class Packaging Group:	
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis	ethod: in accordance mation Hazard ion: Corrosive	Code: 1122			
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis	ethod: in accordance mation Hazard ion: Corrosive nts: Sodium hy	Code: 1122 liquid, n.o.s.			
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy	Code: 1122 liquid, n.o.s.			
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Info Proposition 65: N	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ormation ot Listed.	Code: 1122 liquid, n.o.s.	ID Number: UN176		
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Info Proposition 65: N	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ormation ot Listed.	Code: 1122 liquid, n.o.s. droxide, Sodium silicate	ID Number: UN176		
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Info Proposition 65: N * This product is s	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ormation lot Listed. subject to the r	Code: 1122 liquid, n.o.s. droxide, Sodium silicate	ID Number: UN176		
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Infor Proposition 65: N * This product is s EPA: No	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ormation ot Listed. subject to the r	Code: 1122 liquid, n.o.s. droxide, Sodium silicate	ID Number: UN176		
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Infor Proposition 65: N * This product is s EPA: No 16 Other Informat HMIS/NFPA Hazar The information con	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ermation lot Listed. subject to the relation d Rating: tained herein is regarding the accordance	Code: 1122 liquid, n.o.s. droxide, Sodium silicate eporting requirements of S ealth 2 Flammabil based on the data available curacy of this data or the res	ID Number: UN176 ARA Title III. ity 0 Reactito us. It is believed to	Packaging Group: vity 0 be correct. No warrant	iy, expressed
13 Disposal Consi Waste Disposal M Dispose of waste 14 Transport Infor HAZMAT: Yes Hazardous Divis Hazardous Conte 15 Regulatory Info Proposition 65: N * This product is s EPA: No 16 Other Informat HMIS/NFPA Hazar The information con or implied, is made to	ethod: e in accordance mation Hazard ion: Corrosive nts: Sodium hy ormation lot Listed. subject to the re tained herein is regarding the accidistributor, Brace	Code: 1122 liquid, n.o.s. droxide, Sodium silicate eporting requirements of S ealth 2 Flammabil based on the data available curacy of this data or the res	ID Number: UN176 ARA Title III. ity 0 Reactito us. It is believed to	Packaging Group: vity 0 be correct. No warrant	iy, expressed