CG2435

## MATERIAL SAFETY DATA SHEET

(Prepared According to 29 CFR 1910.1200)

HMIS HAZARDOUS MATERIALS **IDENTIFICATION SYSTEM** 

Health.... 3

Flammability.... 0 Physical Hazard.... 1 Protection.... D

A = Safety Glasses F = C + Dust Mask B = A + Gloves G = B + Respirator C = B + ApronH = F + Goggles D = C + Face Shield I = B + Respirator E = B + Dust Mask X = Ask Supervisor

4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant

SECTION I - PRODUCT IDENTIFICATION

Section(s) changed: I, II, III, X Effective date: September 26, 2008

PRODUCT NAME: POWER-BREAK GENERIC NAME: Builder/Break DISTRIBUTORS NAME:

Product Code: 700

CHEMICAL FAMILY: Alkaline Detergent FORMULA: Proprietary Mixture DISTRIBUTORS ADDRESS:

INFORMATION PHONE NUMBER: 314-771-6600 EMERGENCY PHONE NUMBER IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE OR ACCIDENT: CHEMTREC 800-424-9300

Supersedes date: July 14, 2004

PROPER SHIPPING DESCRIPTION: Caustic Alkali Liquid, n.o.s. (Contains sodium hydroxide), 8, UN1719, II LABEL: Corrosive

**SECTION II - HAZARDOUS INGREDIENTS** 

Wt%

<25

CHEMICAL NAME Sodium Hydroxide

CAS No. 1310-73-2 OSHA PEL 2 mg/m<sup>3</sup>

ACGIH TLV 2 mg/m³

OTHER

The information & recommendations set forth herein are presented in good faith & believed to be current & reliable. The manufacturer makes no representation as to the completeness or accuracy thereof & supplies information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will the manufacturer be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which it refers

SECTION III - PHYSICAL/CHEMICAL DATA

Boiling Point (°F): 210 Specific Gravity: 1.23 Vapor Pressure (mm Hg): 17 Lbs/Gal Density: 10.28 Vapor Density (Air=1): 0.62 pH Concentrate: 14

Evaporation Rate: (Water=1): GT 1.00 pH Use Dilution: 13 Solubility in Water: Complete

Physical Description: Clear Colorless Thin Liquid Mild Odor

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used): None LIMITS: LEL: NA EXTINGUISHING MEDIA: Water spray or fog, foam, dry chemical, carbon dioxide, alcohol foam,

if product is involved.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid exposure to furnes or vapors. Wear selfcontained positive pressurized breathing apparatus MSHA/NIOSH Approved or equivalent to

UNUSUAL FIRE & EXPLOSION HAZARD: Use water spray to cool adjacent fire exposed containers. Product will not burn but may splatter if temperature exceeds boiling point.

SECTION V - REACTIVITY DATA

Stability: Stable. Hazardous Polymerization: Will not occur. Incompatibility (Materials to Avoid): Strong Acids.

Hazardous Decomposition Products: If burned, normal combustion products:

Carbon Dioxide, Carbon Monoxide; Nitrous Oxides.

SECTION VI - STORAGE & HANDLING INFORMATION

KEEP OUT OF REACH OF CHILDREN, DANGER, POISON, Avoid all contact. Store upright in original closed container.

Other Precautions: Do not get in eyes, on skin or on clothing. Remove &

wash contaminated clothing before reuse.

SECTION VII - HEALTH HAZARDS AND FIRST AID

Carcinogenicity: ΝĒ

NTP? NË

OSHA REGULATED? IARC Monographs? NE

EFFECTS OF OVEREXPOSURE: EMERGENCY FIRST AID PROCEDURES:

SKIN: Severe burns SKIN: Wash with soap & water for 15 minutes. See physician if burning persists.

EYES: Severe burns EYES: Flush with flowing water for 15 minutes & see physician. INHALATION: Severe burns

INHALATION: Remove to fresh air. If breathing has stopped, apply suitable artificial respiration. Get medical help. INGESTION: Severe burns INGESTION: Give milk or water to dilute material; DO NOT induce vomiting. Avoid alcohol. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS

PERSON

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: (Specify type) Normal room ventilation

VENTILATION: Local exhaust preferred. Mechanical (general) at point of mist acceptable. Avoid breathing vapor or spray.

PROTECTIVE GLOVES: Impervious rubber, alkali proof.

EYE PROTECTION: Splash proof chemical goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Impervious rubber boots & apron, Eye wash facilities, Safety Shower,

WORK/HYGIENIC PRACTICES: Practice good personal hygiene. Wash after handling. Shower at end of work period.

SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Mop up & flush to sewer with plenty of water. Floors may be slippery. Use care to avoid falls. Neutralize with dilute acid or sodium bicarbonate.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State & Local regulations

SECTION X - ADDITIONAL FEDERAL REGULATIONS

SARA TITLE III (EPCRA) NOTIFICATION: Does not contain chemicals subject to the reporting requirements of Section 302, 304, or 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT (CERCLA) NOTIFICATION: SODIUM HYDROXIDE For more information, consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68.

NE - Not Established NA - Not Applicable GT - Greater Than

Manufactured by:Intercon Chemical Company 1100 Central Industrial Drive, St. Louis, MO 63110