

Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) SPEED STRIPPER CONCENTRATE (Product No. 6, Twist 'n Fill(tm) System)

MANUFACTURER: 3M

DIVISION: Building & Commercial Services Division

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/20/09 Supercedes Date: 06/09/08

Document Group: 11-9287-1

Product Use:

Intended Use:

Hard Floor Maintenance

SECTION 2: INGREDIENTS

<u>Ingredient</u>	C.A.S. No.	% by Wt
BENZYL ALCOHOL	100-51-6	30 - 45
ETHANOLAMINE	141-43-5	30 - 45
CAPRYLIC ACID	124-07-2	10 - 30
CAPRIC ACID	334-48-5	7 - 13
POLYETHYLENE GLYCOL TRIMETHYL NONYL ETHER	60828-78-6	1 - 5
LAURIC ACID	143-07-7	< 0.5
CAPROIC ACID	142-62-1	< 0.5
I-HYDROXYETHANE-1,1-DIPHOSPHONIC ACID	2809-21-4	< 0.5
FRAGRANCE COMPOUND	Trade Secret	< 0.5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Dark blue color; soapy fragrance

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: May cause chemical eye burns. May cause chemical skin burns.

May cause chemical gastrointestinal burns. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

May be harmful if absorbed through skin.

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

A 3M Product Environmental Data Sheet (PED) is available.

A conservative assessment of this product indicates that its use and proper disposal are likely to present a low environmental risk. Potential use and misuse are unlikely to cause components to enter the environment in quantities or by routes that could cause adverse environmental impacts.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water for at least 15 minutes. Get immediate medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Flash Point

> 220 °F [Test Method: Tagliabue Closed Cup]

OSHA Flammability Classification:

Class IIIB Combustible Liquid

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Non-flammable: ordinary combustible material.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures:

Dispose of collected material as soon as possible.

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Keep out of the reach of children. This product is not intended to be used without prior dilution as specified on the product label. Avoid breathing of vapors, mists or spray. Avoid skin contact, Avoid eye contact with vapors, mists, or spray. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

7.2 STORAGE

Keep container in well-ventilated area.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8,1 ENGINEERING CONTROLS

Use in a well-ventilated area. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, special ventilation is not required.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray. NOTE: When used as directed and diluted and dispensed with a TWIST in FILL(TM) Chemical Dispenser, eye contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, the following eye protection is recommended: Indirect Vented Goggles, Full-face shield.

8.2.2 Skin Protection

Avoid skin contact. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, skin contact with the concentrate is not expected to occur,

If the product is not used with the Twist in Fill system or if there is an accidental release, select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material is recommended: Butyl Rubber, Polyethylene/Ethylene Vinyl Alcohol. The following protective clothing material is recommended: Apron - Polyethylene ethylene vinyl alcohol, Boots - Neoprene.

8,2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, respiratory protection is not required.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Fullface supplied-air respirator. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredieut	Authority	Type	<u>Limit</u>	Additional Information
BENZYL ALCOHOL	ATHA	TWA	10 ppm	
ETHANOLAMINE	ACGIH	TWA	3 p pm	
ETHANOLAMINE	ACGIH	STEL	6 ppm	
ETHANOLAMINE	OSHA	TWA	3 ppm	Table Z-1A
ETHANOLAMINE	OSHA	STEL	бррт	Table Z-1A
POLYETHYLENE GLYCOLS	Alha	TWA, as aerosol	10 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:

General Physical Form:

Flash Point

Boiling point

Vapor Density

Vapor Pressure

Specific Gravity

pН

Solubility in Water **Evaporation rate** Volatile Organic Compounds

Percent volatile VOC Less H2O & Exempt Solvents

Viscosity

Dark blue color; soapy fragrance

> 220 °F [Test Method: Tagliabue Closed Cup]

> 200 °F

>1 [Ref Std: AIR=1]

<=27 psia [@ 131 °F] [Details: MITS data]

1 [Ref Std: WATER=1]

10.5 - 11.5

Complete

> 1 [Ref Std: WATER=1]

60 - 90 % [Test Method: calculated per CARB title 2]

No Data Available

600 - 900 g/l [Test Method; calculated per CARB title 2]

< 100 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid None known 10.2 Materials to avoid None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance Carbon monoxide

Carbon dioxide Oxides of Nitrogen Condition
During Combustion
During Combustion

During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

CHEMICAL FATE INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

1D Number 70-0710-0963-6

UPC 00-48011-23905-2

ID Number 70-0710-6561-2

UPC 00-48011-19208-1

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

STATE REGULATIONS

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this product are listed on the Australian Inventory of Chemical Substances.

All the components of this product are listed on China's Inventory of Chemical Substances.

The components of this product are in compliance with notification requirements in the Philippines.

The components of this product are listed on the Canadian Domestic Substances List,

INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. ()SHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 3 Flammability: 1 Reactivity: 0 Special Hazards: None

Acid/Base: Alkaline

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 3 Flammability: 1 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Copyright was modified.

Section 14: ID Number(s) and/or UPC(s) Template 1 was added.

10.1 Conditions to avoid was added.

10.2 Materials to avoid was added.

Section 6: Release measures information was added.

Section 6: Release measures information was added.

Section 10: Materials to avoid physical property was added.

Section 10: Conditions to avoid physical property was added.

Section 6: Release measures information was deleted.

Section 10: Materials and conditions to avoid physical property was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



Transport Information Document

Date: November 11, 2009

3M ID Number: 70-0710-0963-6

Product Description: 3M(TM) Speed Stripper Concentrate 6H, Black Cap, 2 Liter, 6/case

Transport Protective Service: PROTECTIVE SERVICE NOT REQUIRED

NMFC Item: 048580

NMFC Sub: 03

NMFC Class: 055.0

Flash Point (Closed-cup): 220°F/104°C

CONSUMER COMMODITY, ORM-D	See And	
CONSUMER COMMODITY, ORM-D	The same of the sa	
UN2491, ETHANOLAMINE SOLUTION, 8, III		Carlos de la Carlo
		: /s
UN2491, ETHANOLAMINE SOLUTION, 8, III		

The classification is authorized by the Competent Authority of the United States of America and may not meet the requirements of other competent authorities.

These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING, OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

For Transport Information, please visit 3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501 for assistance.