



Spartan Chemical Company, Inc.
Material Safety Data Sheet

C42675

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
LAMINATE LIGHTS ENDURABASE
 Product Number: 4033

Product Division:
Janitorial

Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
 Medical Emergency: **1-(888)-314-6171 (24 hours)**
 Chemical Leak/Spil Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1 - Slight Fire: 0 - Minimal Reactivity: 0 - Minimal	Health: *1 - Slight; Chronic Hazard Fire: 0 - Minimal Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Acrylic polymer	20-25	Proprietary	Not Established	Not Established	Not Established	No
*Diethylene glycol ethyl ether	1-5	111-90-0	140 (AIHA)	Not Established	Not Established	No
Tributoxyethyl phosphate	1-5	78-51-3	Not Established	Not Established	Not Established	No
Dipropylene glycol methyl ether	1-5	34590-94-8	600 [skin]	900 (NIOSH)	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 8 - 9	Specific Gravity (H ₂ O=1): 1.027
Evaporation Rate (but. ace.=1): <1	Percent Solid by Weight: 30-40
Physical State: Liquid	
Appearance & Odor: Translucent emulsion, slight ammoniacal odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Material can splatter above 212 F. Dried product can burn. Combustion products are toxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established

Primary Routes of Entry: Inhalation, Skin Contact, Eyes and Oral.

Effects of Overexposure: **Causes mild eye irritation:** Symptoms may include pain, redness, swelling and tearing.
 Conditions to Avoid: **May cause skin irritation:** Symptoms may include redness, pain and swelling.
Harmful if swallowed: Symptoms may include nausea, vomiting, pain and diarrhea.
Inhalation of vapors may cause respiratory irritation, headache and nausea.
 Contains diethylene glycol monoethyl ether which may cause central nervous system depression, liver and kidney impairment.
 Contains tributoxylethyl phosphate which may cause nervous system effects such as ataxia, breathing abnormalities and tremors with prolonged or repeated contact.
Avoid contact with eyes and skin. Avoid breathing product vapors or mist. Use with adequate ventilation. Do not taste or swallow. Wash thoroughly after handling.

Conditions Aggravated by Use: Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.

Emergency & First Aid Procedures:

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.

Skin: Remove contaminated clothing. Flush skin thoroughly with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.

Ingestion: Do not induce vomiting unless told to do so by physician or poison control center. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.

Inhalation: In case of respiratory irritation; move person to fresh air. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability: Stable

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition may yield styrene and acrylic monomers.

Hazardous Polymerization: Will Not Occur.

SECTION VII: SPILL OR LEAK PROCEDURES**Steps to be Taken in Case**

Material is Released or Spilled: Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain large spills with inert material and transfer liquid to containers for recovery or disposal.

Waste Disposal Method: Assure conformance with federal, state and local regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not normally needed when good ventilation is provided. However, if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, use of a NIOSH approved respirator suitable for the conditions of use and substances in Section II should be considered.

Ventilation: Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.

Protective Gloves(Specify Type): Impervious gloves are recommended for prolonged or repeated contact.

Eye Protection(Specify Type): Safety glasses or splash goggles are recommended to prevent eye contact.

Other Protective Equipment: For further guidance see 29 CFR 1910.132-138.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep from freezing.

Other Precautions: Keep out of reach of children.

© SCC 06/30/2005

Name: Ronald T. Cook

Title: Manager, Regulatory Affairs

LAMINATE LIGHTS ENDURBASE

Effective Date: 06/30/2005

Supercedes: 11/20/2003

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Update Section IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.