Preparation date: 2010-04-26





LinoSAFE Linoleum/Stone Stripper

HMIS		NFPA	Personal protective equipment	
Health	3	3	and some	
Fire Hazard	0	0		
Reactivity	0	0		

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LinoSAFE Linoleum/Stone Stripper

MSDS #:

MS0300433

**Product Code:** 

Version Number: 2

04188

Recommended use:

Industrial/Institutional. Floor stripper.

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 8310 16th St.

Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249

MSDS Internet Address: www.diversey.com

Emergency telephone number:

Canadian Headquarters Diversey, Inc. - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1

Phone: 1-800-668-3131

### 2. HAZARDS IDENTIFICATION

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'I)

**EMERGENCY OVERVIEW** 

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principal routes of exposure:

Eye contact. Skin contact. Inhalation.

Eye contact:

Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Inhalation:

Corrosive. Causes permanent damage. May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion:

Corrosive. Causes burns to mouth, throat and stomach.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
2-butoxyethanol	111-76-2	5 - 10%	470	220 mg/kg	2.21 mg/L (4 h) 450 ppm (4 h)
Diethylene glycol butyl ether	112-34-5	10 - 20%	3384	2700 mg/kg	Not available
Ethylene glycol phenyl ether	122-99-6	5 - 10%	1260	5 mL/kg	Not available
Monoethanolamine	141-43-5	0.1 - 1.5%	1720	1 mL/kg 1025 mg/kg	Not available

# 4. FIRST AID MEASURES

Eye contact:

Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Inhalation:

Immediately flush with plenty of water for 15-20 minutes . Get medical attention immediately.

Ingestion:

If breathing is affected, remove to fresh air. Get medical attention immediately.

If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

**Aggravated Medical Conditions:** 

Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc.,

may be more susceptible to irritating effects

LinoSAFE Linoleum/Stone Stripper

1 of 4

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards:

Not applicable

Unusual hazards:

Corrosive material (See sections 8 and 10).

Specific methods:

No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Environmental precautions and clean-up methods: Put on appropriate personal protective equipment (see Section 8.).

Use appropriate containment to avoid environmental contamination. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Keep in suitable and closed

containers for disposal. Use a water rinse for final clean-up.

#### 7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERICAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Chemical-resistant gloves

Skin and body protection: Respiratory protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin 50 ppm (TWA) 240 mg/m³ (TWA)	75 ppm (STEL) 360 mg/m³ (STEL) 26 ppm (TWA) 120 mg/m³ (TWA)
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)	6 ppm (STEL) 15 mg/m³ (STEL) 3 ppm (TWA) 8 mg/m³ (TWA)

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Appearance: Liquid Specific gravity: 1.01

Vapor density: No information available Boiling point/range: Not determined Decomposition temperature: Not determined

Solubility: Completely Soluble

Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Bulk density: No information available Evaporation Rate No information available

Color: Colorless Odor: Solvent

Melting point/range: Not determined

Autoignition temperature: No information available

Density: 8.42 lbs/gal 1.01 Kg/L Flash point: > 200 °F > 93.4 °C Viscosity:No information available

LinoSAFE Linoleum/Stone Stripper

Elemental Phosphorus: 0 % by wt.

VOC: 9 % \*

pH: 9.8

Dilution pH: No information available.

Explosion limits: - upper: Not determined - lower: Not determined

\* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

#### 10. STABILITY AND REACTIVITY

Stability:

Polymerization:

The product is stable Hazardous polymerization does not occur

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid:

Acids. Strong oxidising agents.

Conditions to avoid:

Do not mix with any other product or chemical.

#### 11. TOXICOLOGICAL INFORMATION

Corrosive Oral LD50 estimated to be between 4000 - 5000 mg/kg

Acute toxicity: Component Information:

See Section 3

Chronic toxicity:

None known

Specific effects

Carcinogenic effects:

None known

Mutagenic effects:

None known

Reproductive toxicity: Target organ effects:

None known None known

#### 12. ECOLOGICAL INFORMATION

**Environmental Information:** 

No data available

### 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations.

### 14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

#### 15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

# RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
2-butoxyethanol	111-76-2	X	X	X	X
Diethylene glycol butyl ether	112-34-5	-			
Ethylene glycol phenyl ether	122-99-6				
Sodium xylene sulfonate	1300-72-7	(=)	-	141	-
Monoethanolamine	141-43-5	X	X	Х	Х
Water	7732-18-5	2		_	-

#### CERCLA/ SARA

LinoSAFE Linoleum/Stone Stripper

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol	111-76-2	5 - 10%			X
Ethylene glycol phenyl ether	122-99-6	5 - 10%		1	X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
2-butoxyethanol	X		
Ethylene glycol phenyl ether	X		

SARA 311/312 Hazard Categories Immediate:

Delayed:

Fire:

Reactivity:

Sudden Release of Pressure: Canada

WHMIS hazard class: E Corrosive material



Х

# 16. OTHER INFORMATION

Reason for revision: Prepared by: Additional advice:

Not applicable NAPRAC

None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.