

CX 8000

STONE PRO

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Stone Pro Maintenance Crystallizer PRODUCT CODE: SPMC
CHEMICAL NAME: Acrylic blend CAS #: Blend, no single CAS # applies
DOT HAZARD CLASS: UN 2856 DATE: February 19, 2005

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	TLV (UNITS)	PEL
Sodium Hexafluorosilicate	16949658	2.5 MG/M3	2.5 MG/M3

SECTION III - PHYSICAL DATA

BOILING POINT: (F) 212 SOLUBILITY: Complete pH: .5-2.0
VOC: 30 g/L VAPOR DENSITY: N/A VAPOR PRESSURE: N/A
EVAPORATION RATE (WATER = 1); >1 SPECIFIC GRAVITY: 1.1
APPEARANCE & ODOR: Opaque pink liquid with acrid odor.

SECTION IV - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT: N/A
FLAMMABLE LIMITS: N/A LOWER: N/A UPPER: N/A
FIRE/EXPLOSION HAZARDS: None
EXTINGUISHING MEDIA: Foam, CO2, dry chemical
FIRE FIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

SECTION V - HEALTH HAZARD INFORMATION

PERMISSIBLE EXPOSURE LEVEL: ND
EYES: Will cause irritation and redness.
SKIN: Severe irritation.
INHALATION: Inhalation of mist may cause respiratory irritation.
INGESTION: Will cause severe gastrointestinal irritation.
THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA
HMIS HAZARD CLASS: Health = 3 Flammability = 0 Reactivity = 0 Other = NA
Ranking: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

FIRST AID

EYE CONTACT: Flush with water for 15 minutes lifting eyelids. Get medical attention immediately
SKIN CONTACT: Wash with water and treat with any moisturizing cream.
INHALATION: Remove victim to fresh air. Administer artificial respiration if breathing ceases. Get medical attention immediately.
INGESTION: Do not induce vomiting. Give lots of water. Give milk of magnesia. Call a physician.

SECTION VI - REACTIVITY INFORMATION

STABILITY: Stable
REACTIVITY: None will occur
HAZARDOUS DECOMPOSITION INGREDIENTS: N/A
HAZARDOUS POLYMERIZATION: Will not occur

STONE PRO

SECTION VII - SPILL, LEAK AND DISPOSAL PROCEDURES

SMALL SPILLS: Mop, sweep or absorb. Transport to non-hazardous land fill.

LARGE SPILLS: Mop, sweep, or absorb. Transport to non-hazardous land fill.

DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

SECTION VIII - SPECIAL PROTECTIVE EQUIPMENT

EYE AND FACIAL: Wear chemical splash goggles.

SKIN: Vinyl, rubber, or nitrile gloves should be used.

RESPIRATORY: Provide OSHA approved mists respirator.

VENTILATION: Local mechanical ventilation to keep TLV'S below recommended levels.

OTHER: Wear protective apron, boots, and clothing.

SECTION IX - SPECIAL PRECAUTIONS

STORAGE: Store in cool dry well ventilated place

HANDLING: Avoid strong oxidizers and ammonia.

LEGEND: ND, Not Determined; N/A Not Applicable; NA, Not Available.

NOTICE

All information appearing herein is based upon data obtained from chemical manufacturers and or recognized technical sources. While the information is believed to be accurate, Snyder Manufacturing Corporation makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Snyder Manufacturing Corporation's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process