CY 2201

Preparation date: 2009-01-24

100

# **MATERIAL SAFETY DATA SHEET**



Wood Care: Polygrethane 450 Finish

HMIS		NFPA	Personal protective equipment		
Health	2	2			
Fire Hazard	2	2	None / Aucune / Ninguno		
Reactivity	0	0			
Version Number: 1	<u>"</u>		Cuiiii		

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Wood Care: Polyurethane 450 Finish MSDS #: MS0300319 **Product Code:** 

5142201 Recommended use: industrial/institutional. Floor care.

Manufacturer, importer, supplier:

**US Headquarters** JohnsonDiversey, Inc.

8310 16th St. Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249 MSDS Internet Address: www.johnsondiversey.com

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle

Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

# 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

CAUTION. CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE LIQUID AND VAPOR.

Principle routes of exposure:

Eye contact:

Skin contact:

Inhalation:

Ingestion:

Eye contact. Skin contact. Inhalation. Moderately irritating to the eyes. Moderately irritating to the skin.

May cause central nervous system effects, including headache, and dizziness.

May cause irritation to mouth, throat and stomach.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients	<del></del> -				
Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Aliphatic hydrocarbons	64742-47-8	50 - 60%	15000	>2000 mg/kg	>5.2 mg/L (4 h)

# 4. FIRST AID MEASURES

Eye contact:

Skin contact: Inhalation:

Flush immediately with plenty of water. If irritation persists, get medical attention. Flush immediately with plenty of water, if irritation persists, get medical attention. If breathing is affected, remove to fresh air.

78.445

Ingestion:

if swallowed, give a cupful of water or milk.

Aggravated Medical Conditions:

Persons with pre-existing skin disorders may be more susceptable to irritating effects.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Specific hazards:

Use dry chemical, CO2, water spray or "alcohol" foam.

Keep product and empty container away from heat and sources of ignition.

Unusual hazards:

None know n

Specific methods:

No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NiOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

S.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

20024

Use personal protective equipment. Remove all sources of ignition. Ventilate the area.

Wood Care: Polyurethane 450 Finish

1 of 3

#### 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions and clean-up methods:

Keep out of water supplies and sewers. Prevent product from entering drains. Soak up with oil absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

## 7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. COMBUSTIBLE LIQUID AND VA POR. Keep away from open flames, hot surfaces and sources of ignition. Use only in well-ventilated areas, HANDLING OF WASTE MATERIALS: Used finish materials (e.g.clean-up rags, steel wool, tacking towels) and sanding dust can spontaneously ignite if improperly discarded. Do not store waste finish materials or sanding dust in a pile or discard into the regular trash. Instead, immediately place all waste materials into a water-filled metal container and discard according to local, state and federal regulations.. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

#### 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

No special ventilation requirements. General room ventilation is adequate.

Personal Protective Equipment

Hygiene measures:

Eye protection: Hand protection: Skin and body protection: Respiratory protection:

No special requirements under normal use conditions. No special requirements under normal use conditions No special requirements under normal use conditions. No special requirements under normal use conditions.

Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
Aliphatic hydrocarbons	64742-47-8		1200 mg/m³	

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Liquid

pH: Appearance: Not applicable Liquid Milky Amber

Color: Odor: Specific gravity:

Solvent 0.89

Density:

7.42 lbs/gal

VOC:

450g/L (40 CFR §59,400)

Flash point:

110°F 43.3°C

Solubility: Viscosity: Insoluble 260 S.U.S. Bulk density:

Dilution pH: Vapor density: **Evaporation Rate** 

Boiling point/range: Melting point/range:

Decomposition temperature: Autoignition temperature:

Partition coefficient (n-octanol/water): No information available Solubility in other solvents: No information available

Hemental Phosphorus:

0 %P

No information available

No information available.

No information available

No information available

No information available

**有机能均衡** 

Not determined

Not determined

Not determined

#### 10. STABILITY AND REACTIVITY

Stability:

Polymerization:

The product is stable

Hazardous polymerization does not occur

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid: Conditions to avoid: Strong oxidising agents. Do not mix with any other product or chemical.

Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Oral LD50 estimated to be greater than 5000 mg/kg Dermal LD50 estimated to be > 2000 mg/kg

Component Information:

See Section 3

Chronic toxicity:

None know n

Specific effects

Carcinogenic effects: Mutagenic effects: Reproductive toxicity: Target organ effects:

None know n None know n None know n None know n

### 12. ECOLOGICAL INFORMATION

Environmental Information:

No data available

Wood Care: Polyurethane 450 Finish

2 of 3

## 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of brushes and rags used for processing of the product as hazardous waste. Undiluted product is regulated under environmental and transportation laws as a corrosive waste.

### 14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

## 15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: Canada (DSL/NDSL), U.S.A. (TSCA).

U.S. Regulations

1146

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Aliphatic hydrocarbons	64742-47-8			-	- 12137 63
Proprietary Proprietary	TS*	-	-		-

#### CERCLA/ SARA

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: X
Reactivity: Sudden Release of Pressure: -

Canada

WHM15 hazard class: B3 Combustible liquid , D2B Toxic materials.



Ingredient(s)	CAS#	NPRI
Aliphatic hydrocarbons	64742-47-8	, , , , , , , , , , , , , , , , , , ,

# 16. OTHER INFORMATION

Reason for revision:

Not applicable NAPRAC None

Prepared by: Additional advice:

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.