5142219

MATERIAL SAFETY DATA SHEET

Preparation date: 2009-01-26





Wood Care: Ultra Low Odor Waterbased Sealer

HMIS		NFPA	Personal Per
Health	1	1	Personal protective equipment
Fire Hazard	0	o o	None / Aucune / Ninguno
Reactivity	0	Ö	
Version Number: 1			

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Wood Care: Ultra Low Odor Waterbased Sealer

MSDS#:

MS0300348 5142219

Product Code: Recommended use:

Industrial/Institutional, Floor care.

Manufacturer, importer, supplier:

US Headquarters
JohnsonDiversey, Inc.

8310 16th St.

Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249
MSDS Internet Address:
www.johnsondiversey.com

Emergency telephone number:

Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle

Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

1-800-851-7145 (U.S.); 1-651-917-6133 (Intil)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION, MAY BE MILDLY IRRITATING TO EYES, MAY BE MILDLY IRRITATING TO SKIN.

Principle routes of exposure:

Eye contact: Skin contact: Eye contact. Skin contact. Inhalation. May be mildly irritating to eyes. May be mildly irritating to skin. None.

inhalation: Ingestion:

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients					
Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal -	LC50 Inhalation -
Dipropylene glycol methyl ether		1 - 5%	5135	Rabbit 9500 mg/kg	Rat Not available
Disobutyl adipate	141-04-8	0.1 - 1.5%	5676	Not available	Not available

4. FIRST AID MEASURES

Eye contact: Skin contact: Flush immediately with plenty of water, if irritation develops, get medical attention, Flush immediately with plenty of water, if irritation develops, get medical attention.

Inhalation: Ingestion:

No specific first aid measures are required. No specific first aid measures are required.

Aggravated Medical Conditions:

None known,

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards: Unusual hazards:

Not applicable None known

Specific methods:

No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

on two Days

Use personal protective equipment

Wood Care: Ultra Low Odor Waterbased Sealer

1 of 3

Environmental precautions

and clean-up methods:

6. ACCIDENTAL RELEASE MEASURES

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use a

water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS PERSONAL PROTECTION

Engineering measures to reduce exposure:

No special ventilation requirements. General room ventilation is adequate.

Personal Protective Equipment

Eye protection: Hand protection: Skin and body protection:

No special requirements under normal use conditions. No special requirements under normal use conditions No special requirements under normal use conditions. No special requirements under normal use conditions.

Respiratory protection: Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

Ingredient(s) Dipropylene glycol methyl ether	CAS # 34590-94-8	ACGIH 150 ppm (STEL) 100 ppm (TWA)	OSHA Skin 100 ppm (TWA) 600 mg/m² (TWA)	900 mg/m² (STEL) 150 ppm (STEL) 100 ppm (TWA)
			<u></u>	60 mg/m³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Liquid 8.0

Appearance: Color:

Liquid Amber

Odor: Specific gravity:

Sw eet 1.04

Density: VOC:

pH:

8.67 lbs/gal

Flash point:

100g/L (40 CFR §59.400)

Solubility:

>200°F >93.34°C

Partially Soluble No information available

Viscosity:

Bulk density:

Dilution pH;

Vapor density: Evaporation Rate

Boiling point/range: Melting point/range:

Decomposition temperature: Autoignition temperature:

Partition coefficient (n-octanol/water): No information available

Solubility In other solvents:

Bemental Phosphorus:

No information available

Not applicable

No information available No information available

Not determined Not determined Not determined

No information available

No information available

0 %P

10. STABILITY AND REACTIVITY

Stability:

Polymerization:

The product is stable

Hazardous polymerization does not occur

Hazardous decomposition products:

None reasonably foreseeable.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Component Information:

Oral LD50 estimated to be greater than 5000 mg/kg Dermal LD50 estimated to be > 2000 mg/kg See Section 3

Chronic toxicity:

None know n Specific effects Carcinogenic effects:

Mutagenic effects: Reproductive toxicity: Target organ effects:

None know n

None know n None know n None know n

12. ECOLOGICAL INFORMATION

Environmental information:

No data available

13. DISPOSAL CONSIDERATIONS

Wood Care: Ultra Low Odor Waterbased Sealer

2 of 3

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations

FORESCO CHESTON

14. TRANSPORT INFORMATION

DOT/TDG: Hease refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS#	MARTK:	NURTK:	PARTK:	RIRTK:
Dipropylene glycol methyl ether Water	34590-94-8	X	X	X	X
Disobutyl adipate	7732-18-5 141-04-8	 	<u> </u>		
Proprietary	TS*	-	<u> </u>		

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs) Section 302 TPQ (lb	Section 313
Dipropylene glycol methyl ether	34590-94-8	1 - 5%	Gettion 302 (POIII)	SI SECTION 313
•				^

ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Dipropylene glycol methyl ether	x		- OTTAL TIONEY FORMLANDS

SARA 311/312 Hazard Categories

immediate:

De layed:

Fire:

Reactivity:

Sudden Release of Pressure:

Canada

WHITS hazard class: Non-controlled.

Ingredient(s)	CAS#	MDDI
Dipropylene glycol methyl ether		<u>NPRI</u>
- Frappiene gif ooi metrif (dirie)	34590-94-8	X

16. OTHER INFORMATION

Reason for revision:

Prepared by:

Not applicable NAPRAC

Additional advice:

None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Wood Care: Ultra Low Odor Waterbased Sealer