

SECTION VI -- HEALTH HAZARD DATA continued

Signs and Symptoms of Exposure: Prolonged contact causes skin burns. May cause nose and throat irritation. Swallowing can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Vapor harmful - overexposure may affect the brain or nervous system causing dizziness, headache or nausea. May also cause allergic skin reactions.

Medical Conditions Generally Aggravated by Exposure: Pre-existing eye, skin and respiratory disorders.

Emergency and First Aid Procedures: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove all contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean contaminated shoes. If swallowed, do not induce vomiting. Call a physician.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: If spilled, contain spilled material and remove with inert absorbent and non-sparking tools. Dispose of contaminated absorbent, container and unused contents in accordance with Federal, State and Local regulations. Remove all sources of ignition (flames, hot surfaces; electric, static or friction sparks). Avoid breathing vapors. Ventilate area. Do not smoke when working with product. Do not pick up solution with automatic scrubber or wet pick-up vacuum.

Waste Disposal Method: Dispose of in accordance with state or local regulations. EPA Hazardous Waste Classification: Ignitable Liquid. Incinerate in approved facility; do not incinerate closed container. Do not dispose of in storm drains or waterways.

Precautions To Be Taken In Handling And Storing: Since empty packages retain product residue, follow label warnings even after package is empty. Keep container closed when not in use. Do not store at temperatures over 100°F. Notice: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building. Notice: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

Other Precautions: Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **USE ONLY WITH ADEQUATE VENTILATION.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor / mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally. This product contains no reportable quantities of toxic chemicals subject to reporting requirements of Section 313 of SARA Title III Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR Part 372.

SECTION VIII -- CONTROL MEASURES:

Respiratory Protection (Specify Type): Wear appropriate, properly fitted respirator (NIOSH and MSHA approved) unless air monitoring demonstrates vapor or mist levels are below applicable limits.

Ventilation: At least 10 air chgs/hr recommended.

Local Exhaust = Recommended **Mechanical (General) =** Recommended **Special =** N/A **Other =** N/A

Protective Gloves: Solvent impervious rubber gloves **Eye Protection:** Solvent resistant eyewear with splash guards

Other Protective Clothing or Equipment: Solvent impermeable clothing

Work / Hygienic Practices: Wash clothing before reuse. Thoroughly clean contaminated shoes.

SECTION IX - TRANSPORTATION INFORMATION:

Applicable regulations: CFR = no IMCO = yes IATA = yes

Proper shipping name for air and foreign water: Paint 3, UN1263, III

Proper shipping name for highway: Varnish

UN No.: not applicable for highway **Limited Qty.:** not applicable **Hazard class:** not applicable for highway

Labels required: not required for highway **DOT Exception:** not applicable

EPA Hazardous waste characteristics:

Ignitability = yes; **Corrosivity =** not applicable; **Reactivity =** not applicable

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.