H103154

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910 1200 and OSHA Form 174 IDENTITY AND DISTRIBUTOR'S INFORMATION HMIS Rating: Health-2, Flammability1; Reactivity-0; Personal Protection-B NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special-0 DOT Hazard Classification: ORM-D Manufactured For: Hillyard Industries, Inc. Identity (trade name as used on label): Address: 302 N. 4ⁱⁿ Street LUSTRE- MIST FURNITURE POLISH, #HIL0103154 St. Joseph, MO 64501 Address: Revision- 11 (816)-233-1321 ext. 8285 or http://www.hillyard.com MSDS Number: A00134 Phone: Prepared By: AH/IB Date Prepared: 9/10/01 Emergency Response Number: Chemtrec 1-800-424-9300 Information Calls: (770) 422-2071 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION OSHA PEL ACGIH Carcinogen COMPONENTS-CHEMICAL NAMES AND COMMON NAMES SARA CAS Number III LIST TLV (ppm) Ref. Source * (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) (ppm) 68551-19-9 No NE NF d PETROLEUM DISTILLATES 800 800 d No 75-28-5 ISOBUTANE / PROPANE BLEND 1000 d 74-98-6 No 1000 SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Specific Gravity (H₂O=1): Concentrate Only = 0.954 Boiling Point: N/A Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Vapor Pressure: PSIG @ 70°F (Aerosols): Max.55 Evaporation Rate (BuAc = 1): Slower Vapor Density (Air = 1): N/E Water Reactive: No Solubility in Water: Slight Appearance and Odor: Creamy white spray with lemon fragrance SECTION 3 - FIRE AND EXPLOSION HAZARD DATA Flammability Limits in Air by % in Volume: Auto Ignition Temperature FLAMMABILITY as per USA FLAME PROJECTION TEST % LEL: N/E % UEL: N/E NON-FLAMMABLE N/E (aerosols) EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide. LASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture SECTION 4 - REACTIVITY HAZARD DATA HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT STABILITY [X] STABLE [] UNSTABLE OCCUR. Conditions to Avoid: Open flame, welding arcs, heat, sparks. Incompatibility (Mat. to avoid): Strong oxidizers and alkalies. Hazardous Decomposition Products: CO2, CO, hydrogen chloride SECTION 5 - HEALTH HAZARD DATA]INGESTION [X]SKIN ABSORPTION [] EYE [] NOT HAZARDOUS PRIMARY ROUTES OF ENTRY: [X] INHALATION ACUTE EFFECTS: Inhalation: Excessive inhalation of vapors can be harmful and may cause headaches, dizziness, asphyxia, anesthetic effects and possible unconsciousness. Skin Contact: Mild irritant. Eye Contact: Mild irritant. Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, upper respiratory conditions, liver disease & heart irregularities. **EMERGENCY FIRST AID PROCEDURES** Eye Contact: Flush with water for at least 15 minutes. If irritated, seek medical attention. Skin Contact: Wash with soap and water. Remove contaminated clothing & launder before re-wearing. If imitated, seek medical attention. nhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. SECTION 6 - CONTROL AND PROTECTIVE MEASURES Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved bu U.S. Bureau of Mines for organic марог. Eye Protection: Safety glasses recommended. Protective Gloves: Latex if skin is easily irritated. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Other Protective Clothing & Equipment: None Hyglenic Work Practices: Wash with scap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken in Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

"Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only