

S-SGG; S-SGG5

## Stone Gloss

*Interior and Exterior Gloss & Sealer.*


- V.O.C. Compliant
- Adds Gloss and Sealant Protection to Porous Stone, Saltillo Pavers, Tumbled & Textured Stone, Slate, Limestone, Brick and Travertine
- Easy to Apply
- Resistant to Acid, Oil and Water
- Long-Lasting Form Filler
- Will Not Discolor, Crack or Peel



# STONE PRO

866.786.6310

[www.stoneproonline.com](http://www.stoneproonline.com)



**Product Description:** Adds color, brilliance and gloss to porous stone, rock, saltillo pavers, tumbled & textured stone, slate, limestone, brick, masonry and travertine stone. Provides terrific sealant protection.

**Coverage:** Product will cover approximately 200 to 1,000 ft.<sup>2</sup> per gallon dependant on the porosity of the stone. For best gloss results, additional coats may be needed dependant on stone. Apply using nylon string mop for best consistency.

**Directions:** Always test product in an inconspicuous area to test suitability for intended use. First, be sure the surface is clean, swept and free of wax or sealant contaminants. For best results, use Stone Pro's Formula 51 designed to remove all wax and acrylic coatings. Apply Stone Gloss using a string mop. Apply consistently. Let dry for one hour before applying second coat. Then allow 24 hours before traveling on newly sealed surface.

## SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Stone Pro Stone Gloss  
CHEMICAL NAME: Acrylic blend  
CLASS: Not regulated  
DOT SHIPPING NAME: Not regulated

PRODUCT CODE: SPSG  
CAS #: Blend, no single CAS # applies  
DATE: February 19, 2005

Stone Gloss

DOT HAZARD

## SECTION II - HAZARDOUS INGREDIENTS

| HAZARDOUS INGREDIENTS    | %  | CAS #  | TLV (UNITS) | PEL  |
|--------------------------|----|--------|-------------|------|
| 2(butyoxyethoxy) Ethanol | <5 | 112345 | None        | None |

## SECTION III - PHYSICAL DATA

BOILING POINT: (F) 212  
VOC: 30 g/L  
EVAPORATION RATE (WATER = 1): >1  
APPEARANCE & ODOR: Opaque white liquid with a solvent odor.

SOLUBILITY: Complete  
VAPOR DENSITY: N/A  
SPECIFIC GRAVITY: 1.025

pH: 7.5-9.0  
VAPOR PRESSURE: N/A

## SECTION IV - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT: N/A  
FLAMMABLE LIMITS: N/A  
FIRE/EXPLOSION HAZARDS: None  
EXTINGUISHING MEDIA: Foam, CO2, dry chemical  
FIRE FIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

LOWER: N/A  
UPPER: N/A

## SECTION V - HEALTH HAZARD INFORMATION

PERMISSIBLE EXPOSURE LEVEL: ND  
EYES: Will cause irritation and redness.  
SKIN: Prolonged contact will cause slight irritation.  
INHALATION: Prolonged inhalation of mist may cause respiratory irritation.  
INGESTION: May cause gastrointestinal irritation.  
THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA  
HMIS HAZARD CLASS: Health = 1 Flammability = 0 Reactivity = 0 Other = NA  
Ranking: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

## FIRST AID

EYE CONTACT: Flush with water for 15 minutes lifting eyelids. Get medical attention immediately  
SKIN CONTACT: Wash with water and treat with any moisturizing cream.  
INHALATION: Remove victim to fresh air. Administer artificial respiration if breathing ceases. Get medical attention immediately.  
INGESTION: Do not induce vomiting. Give lots of water. Give milk of magnesia. Call a physician.

## SECTION VI - REACTIVITY INFORMATION

STABILITY: Stable  
REACTIVITY: None will occur  
HAZARDOUS DECOMPOSITION INGREDIENTS: N/A  
HAZARDOUS POLYMERIZATION: Will not occur

## **SECTION VII - SPILL, LEAK AND DISPOSAL PROCEDURES**

## **Stone Gloss**

SMALL SPILLS: Mop, sweep or absorb. Transport to non-hazardous land fill.

LARGE SPILLS: Mop, sweep, or absorb. Transport to non-hazardous land fill.

DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

## **SECTION VIII - SPECIAL PROTECTIVE EQUIPMENT**

EYE AND FACIAL: Wear chemical splash goggles.

SKIN: Vinyl, rubber, or nitrile gloves should be used.

RESPIRATORY: Provide OSHA approved mists respirator.

VENTILATION: Local mechanical ventilation to keep TLV'S below recommended levels.

OTHER: Wear protective apron, boots, and clothing.

## **SECTION IX - SPECIAL PRECAUTIONS**

STORAGE: Store in cool dry well ventilated place

HANDLING: Avoid strong mineral acids.

LEGEND: ND, Not Determined; N/A Not Applicable; NA, Not Available.

## **NOTICE**

All information appearing herein is based upon data obtained from chemical manufacturers and or recognized technical sources. While the information is believed to be accurate, Snyder Manufacturing Corporation makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Snyder Manufacturing Corporation's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process