

BASELINE PRODUCTS, INC.

SAFETY DATA SHEET

1. Identification

Product identifier: BASELINE STAINLESS STEEL POLISH 9-60

Recommended use: Ready to use metal cleaner and polish

Recommended restrictions: None known.

Manufacturer / supplier: Baseline Products, Inc.
3610 N. Holland-Sylvania Rd.
Toledo, Ohio 43615 USA

Phone: 419-841-6616 **Emergency telephone US:** 1-866-836-8855

2. Hazards Identification

GHS Classification: Classification of this mixture in accordance with paragraph (d) of §1910.1200.
Flammable Aerosols – Category 1
Aspiration Hazard - Category 1

Label Elements:



Symbol:

Signal word:

DANGER

Hazard statements: Extremely flammable aerosol. May be fatal if swallowed and enters airways.

Precautionary statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
See 4. First-Aid Measures for specific treatment.
Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container to an approved disposal facility.

Other Hazards: None known.

3. Composition / Information on Ingredients

Chemical characterization: Mixture of solvents and auxiliary agents.

Hazardous ingredients: The exact percentage of composition has been withheld as a trade secret.

10 - 20% Distillates (Petroleum), Hydrotreated Light CAS 64742-47-8

10 - 20% Butane CAS 106-97-8

2 - 10% Propane CAS 74-98-6

4. First-Aid Measures

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed: Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information: Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media: Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions: Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards: Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Refer to safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling: Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid prolonged or repeated contact with skin. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities: Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 (1000 ppm)

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 (800 ppm)
Propane (CAS 74-98-6)	TWA	1800 mg/m3 (1000 ppm)

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection: Recommended. Not required in normal use.

Hand protection: Recommended. Not required in normal use.

Respiratory protection: If permissible levels are exceeded use NIOSH organic vapor cartridge or an air-supplied respirator.

General hygiene considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state: Gas.

Color: Not available.

Odor threshold: Not available.

pH: 5.6 - 6.6 estimated

Evaporation rate: Not available.

Flammability (solid, gas): Not available.

Upper/lower flammability or explosive limits

Flammability limit – lower (%): Not available.

Explosive limit - lower (%): Not available.

Vapor pressure: 47 - 67 psig @ 70F estimated

Solubility (water): Not available.

Viscosity: Not available.

Decomposition temperature: Not available.

Form: Aerosol.

Odor: Not available.

Initial boiling point/boiling range: 230.76 °F (110.42 °C) estimated

Melting point/freezing point: Not available.

Relative density: Not available.

Flash point: -156.0 °F (-104.4 °C) Propellant estimated

Flammability limit – upper (%): Not available.

Explosive limit - upper (%): Not available.

Vapor density: Not available.

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature: 392 °F (200 °C) estimated

Specific gravity: 0.948 estimated

10. Stability and reactivity

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability: Material is stable under normal conditions.

Possibility of hazardous reactions: None known under conditions of normal use. Hazardous polymerization does not occur.

Conditions to avoid: Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials: Strong oxidizing agents. Fluorine. Chlorine. Nitrates.

Hazardous decomposition products: No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: Droplets of product aspirated into the lungs via ingestion or vomiting may cause a serious chemical pneumonia.

Small quantities reaching lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.

Inhalation: Not available.

Skin contact: No adverse effects due to skin contact are expected.

Eye contact: Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics: If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.

Information on toxicological effects: Acute toxicity May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Acute

Species

Test Results

Dermal

LD50

Rat

6796 mg/kg

Inhalation

LC50

Mouse

8614.3262 mg/l, 120 Minutes estimated

Oral

LD50

Rat

1945.5256 g/kg estimated

Skin corrosion/irritation: Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation: Direct contact with eyes may cause temporary irritation.

Respiratory sensitization: Not a respiratory sensitizer. **Skin sensitization:** Not expected to cause skin sensitization.

Germ cell mutagenicity: No data available.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure: Not classified.

Specific target organ toxicity - repeated exposure: Not classified.

Aspiration hazard: May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Persistence and degradability: No data is available on the degradability of this product.

Bioaccumulative potential: No data available.

Partition coefficient n-octanol / water (log Kow): Butane 2.89

Propane 2.36

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.

Waste from residues/unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging: Empty containers should be taken to an approved waste site for recycling or disposal. Emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT: UN number UN1950 UN proper shipping name Aerosols, flammable Class 2.1

Packing group: Not applicable.

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions: Product meets exception requirements of sec.173.306 and may be shipped as limited quantity.

15. Regulatory information

US federal regulations:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories:

Immediate Hazard – Yes Delayed Hazard - No

Fire Hazard – Yes Pressure Hazard – No Reactivity Hazard - No

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous chemical: No

SARA 313 (TRI reporting): Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane, Propane

Safe Drinking Water Act (SDWA): Not regulated.

US state regulations

US. Massachusetts RTK - Substance List US. Rhode Island RTK

US. New Jersey Worker and Community Right-to-Know Act

US. Pennsylvania Worker and Community Right-to-Know Law

Butane, Propane

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

NPCA Hazardous Material Identification System (HMIS Rating)

Health 1 Flammability 3 Reactivity 0 Personal Protective Eqpt. N/A

Issue date 29-05-2015

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.