## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTR	IBUTOR'S INFORMATI	ON			
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B					
	DOT Hazard Classification: ORM-D				
•	Identity (trade name as used on label):				
Address: Billerica, MA 01862	SSS Chalkboard & Whiteboard Cleaner/ #05156				
·	MSDS Number: A00101 Revision- 16				
Emergency Response Number: 1-800-255-3924					
	Date Prepared: 03/10/05 Prepared By: IB/TR Information Calls: (770)422-2071				
SECTION 1 - MATERIAL IDEN				40000	<b>.</b>
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
2-BUTOXYETHANOL*	111-76-2	Yes*	(ppiii) 25	20	d
2 BOTOXTETTIMOE	111-70-2	168	(skin)	(skin)	u
ETHANOL	64-17-5 No 1000 1000 d				d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
74-98-6			1000	1000	d
*GLYCOL ETHER					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only =0.985					
apor Pressure: PSIG @ 70°F (Aerosols): Max.70  Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E	Evaporation Rate ( = 1): N/E				
Solubility in Water: Soluble Water Reactive: No					
Appearance and Odor: White foam, sassafras fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST  Auto Ignition Temperature  Flammability Limits in Air by % in Volume:					
(aerosols) NON-FLAMMABLE	N/E		: N/É	% UEL:	
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.					
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures	above 130°F or the conta	iner may rı	upture.		
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [ ] UNSTABLE HAZARDOUS POLYMERIZATION [ ] WILL [X] WILL NOT					
OCCUR					
Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.					
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGES	STION [ X ] SKIN ABS	ORPTION	I []EYE	I NOT HA	ZARDOUS
ACUTE EFFECTS:					
Inhalation: Excessive inhalation of vapors can be harmful & may cause headache, dizziness, asphyxia, anesthetic effects & possible					
unconsciousness.					
Eye Contact: Slight irritation.  Skin Contact: Slight irritation.					
Ingestion: Possible chemical pneumonitis if aspirated into lungs.					
<b>CHRONIC EFFECTS:</b> None known to humans. Note: some animal data indicates some reports of anemia, liver, kidney, lung, blood damage wher excessively exposed to 2-butoxyethanol.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
<b>Respiratory Protection (specify type):</b> If vapor concentration exceeds TLV, use respirator approved by NIOSH / MSHA for organic vapors.					
Protective Gloves: Disposable latex gloves suggested.	Eye Protection: Safe	ty glasse:	s recommen	ided.	
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or					
Federal regulations. Dilute with water and flush to sewer.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.					