

Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A00810 MST DUST MOP TREATMENT 20net18
Material number	:	0000000001003402
Manufacturer or supplier's d	leta	lils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers		
For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	characteristic

GHS Classification

Flammable aerosols Gases under pressure Skin irritation	: Category 2 : Liquefied gas : Category 2
GHS Label element	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 H223 Flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P264 Wash skin thoroughly after handling.



Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015
	P280 Wear protective gloves. Response: P302 + P352 IF ON SKIN: Wash P332 + P313 If skin irritation occu attention. P362 Take off contaminated cloth Storage: P410 + P412 Protect from sunlightemperatures exceeding 50 °C/ 1	urs: Get medical advice/ ning and wash before reuse. nt. Do not expose to
Potential Health Effects		
Carcinogenicity:		
IARC	No component of this product presen equal to 0.1% is identified as probably human carcinogen by IARC.	-
ACGIH	No component of this product presen equal to 0.1% is identified as a carcir carcinogen by ACGIH.	
OSHA	No component of this product presen equal to 0.1% is identified as a carcir carcinogen by OSHA.	-
NTP	No component of this product presen equal to 0.1% is identified as a known by NTP.	-

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 20
Distillates (petroleum), hydrotreated light (Vapour and gas)	64742-47-8	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
Stoddard solvent	8052-41-3	>= 5 - < 10
propane	74-98-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	Show this safety data sheet to the doctor in attendar Do not leave the victim unattended.	nce.
lf inhaled	If unconscious place in recovery position and seek r advice. If symptoms persist, call a physician.	nedical
In case of skin contact	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at leas minutes. If on clothes, remove clothes.	.t 15



Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015	
In case of eye contact		: Remove contact lenses. Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.	
If swallowed	: Keep respiratory tract clear. DO NOT induce vomiting unless d physician or poison control center.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products Specific extinguishing methods		Carbon dioxide (CO2) Carbon monoxide Smoke Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for	: Soak up with inert absorbent material (e.g. sand, silica gel,



Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015
containment and cleaning up	acid binder, universal binder, sawdu Sweep up or vacuum up spillage an container for disposal.	

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place.
Materials to avoid	: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light (Vapour and gas)	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm	OSHA P0

Components with workplace control parameters



/ersion 1.0	Revision	Date 02/17/2015	Print	Date 09/28/2015
	I		1,900 mg/m3	
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection	:	In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Safety glasses Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection	:	impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: white
Odour	: characteristic
Odour Threshold	: no data available
рН	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	:
	not applicable
Evaporation rate	: no data available



Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015
Upper explosion limit	: no data available	
Lower explosion limit	: no data available	
Vapour pressure	: no data available	
Relative vapour density	: no data available	
Density	: 0.93 g/cm3	
Solubility(ies)		
Water solubility	: emulsifiable	
Partition coefficient: n- octanol/water	: no data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: no data available	
Viscosity		
Viscosity, kinematic	: no data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Teactions	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

no data available

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:



Version 1.0

Revision Date 02/17/2015

Print Date 09/28/2015

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated heavy naphthenic: Distillates (petroleum), hydrotreated light (Vapour and gas): butane: Stoddard solvent: propane:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

<u>Components:</u>

Distillates (petroleum), hydrotreated light (Vapour and gas): Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: no data available octanol/water



Version 1.0	Revision Date 02/17/2015	Print Date 09/28/2015
<u>Components:</u> butane : Partition coefficient: n- octanol/water	: Pow: 2.89	
Mobility in soil		
no data available		
Other adverse effects		
no data available Product:		
Regulation Remarks	40 CFR Protection of Environment; Stratospheric Ozone - CAA Section Substances This product neither contains, nor w with a Class I or Class II ODS as de Clean Air Act Section 602 (40 CFR + B).	602 Class I vas manufactured afined by the U.S.
Additional ecological information	An environmental hazard cannot be event of unprofessional handling or aquatic life with long lasting effects.	disposal., Harmful to
<u>Components:</u> Distillates (petroleum), hydrotr	eated light (Vapour and gas):	
Additional ecological information	no data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity



Version 1.0

Revision Date 02/17/2015

Print Date 09/28/2015

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazard	s : Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard	
SARA 302	: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.	
The components of this product are reported in the following inventories:		
TSCA DSL	On TSCA Inventory This product contains one or several components that are not on the	

ISCA	On ISCA Inventory
DSL	This product contains one or several components that are not on the
	Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIOC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

SAFETY DATA SHEET



A00810 MST DUST MOP TREATMENT 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 09/28/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

OSUA CUS Labol Information:

Further information NFPA: HMIS III: Flammability HEALTH 3 3 Instability Health FLAMMABILITY 0 3 3 **PHYSICAL HAZARD** 2 0 = not significant, 1 = Slight, Special hazard. 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Hazard pictograms	
Signal w ord Hazard statements	 Warning: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation.
Precautionary statements	: Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and w ater. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and w ash before reuse. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.



Version 1.0

Revision Date 02/17/2015

Print Date 09/28/2015