

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.
Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: VIPER GROUT & CONCRETE SEALER CH05
PRODUCT PURPOSE: GROUT & CONCRETE SEALER
COMPANY IDENTITY: Hydro-Force Manufacturing
COMPANY ADDRESS: 4282 S 590 W
COMPANY CITY: Salt Lake City, UT 84123
COMPANY PHONE: 1-800-948-1779
EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)



SECTION 2. HAZARDS IDENTIFICATION

WARNING!

HAZARD STATEMENTS:

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
H320 Causes eye irritation.

PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove Contact Lenses, if present and easy to do. Continue rinsing.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P332+313 IF SKIN irritation occurs: Get medical advice/attention.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no components contained in this material above 1% that are considered hazardous under 29CFR1910.1200.

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

SECTION 4. FIRST AID MEASURES

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC:

See Section 11 for Symptoms/Effects (acute & chronic).

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing.
Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING:

Rinse mouth. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

COMPANY IDENTITY: Hydro-force Manufacturing
PRODUCT IDENTITY: VIPER GROUT & CONCRETE SEALER

SDS DATE: 03/29/2014
ORIGINAL: 03/29/2014

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES:

Isolate from oxidizers, extreme heat and open flame.

SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:

In case of fire in surroundings, use appropriate extinguishing media.
Do not use water jet.

SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS:

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used.
Do not enter confined fire-space without full bunker gear.
(Helmet with face shield, bunker coats, gloves & rubber boots).

SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS:

Noncombustible.
Closed containers may burst if exposed to extreme heat.
Applying to hot surfaces requires special precautions.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES:

Keep unprotected personnel away.
Wear appropriate personal protective equipment given in Section 8.

ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

METHODS & MATERIAL FOR CONTAINMENT & CLEAN-UP:

Stop spill at source. Dike and contain.
Collect leaking liquid in sealable containers.
Wash away remainder with plenty of water.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Use only with adequate ventilation.
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Isolate from strong oxidants. Do not store above 49 C/120 F.
Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

There are no components contained in this material that are considered hazardous under 29CFR1910.1200. There are no known risks for TWA (OSHA) and TLV (ACGIH).

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

APPROPRIATE ENGINEERING CONTROLS:

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION

LOCAL EXHAUST:	Necessary	MECHANICAL (GENERAL):	Acceptable
SPECIAL:	None	OTHER:	None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles & gloves as a standard practice.

COMPANY IDENTITY: Hydro-Force Manufacturing
 PRODUCT IDENTITY: VIPER GROUT & CONCRETE SEALER

SDS DATE: 03/29/2014
 ORIGINAL: 03/29/2014

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Clear Liquid
ODOR:	None
ODOR THRESHOLD:	Not Available
pH (Neutrality):	7.4
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	> 100 C / > 212 F
FLASH POINT (TEST METHOD):	Not Applicable
EVAPORATION RATE (n-Butyl Acetate=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Non-Combustible
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	Not Applicable
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	17.5
VAPOR DENSITY (air=1):	0.7
GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	1.009
SPECIFIC GRAVITY (Water=1):	1.010
POUNDS/GALLON:	8.413
WATER SOLUBILITY:	Appreciable
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	Not Applicable
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In) :	Not Available
TOTAL VOC'S (TVOC)*:	0.000 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	0.000 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	0.0 Wt%
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	Not Available
VISCOSITY @ 20 C (ASTM D445):	Not Available

* Using CARB (California Air Resources Board Rules).

SECTION 10. STABILITY & REACTIVITY

REACTIVITY & CHEMICAL STABILITY:
 Stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS & CONDITIONS TO AVOID:
 Isolate from extreme heat and open flame.

INCOMPATIBLE MATERIALS:
 Isolate from strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS:
 Carbon Oxides from extreme heating.

HAZARDOUS POLYMERIZATION:
 Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

EYE & SKIN CONTACT:
 Slight irritation to skin, defatting, dermatitis.
 Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:
 Anesthetic. Irritates respiratory tract. Acute overexposure
 can cause serious nervous system depression. Vapor harmful.

SWALLOWING:
 Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:
 Pre-existing disorders of any target organs mentioned in this SDS can be
 aggravated by over-exposure by routes of entry to components of this product.
 Persons with these disorders should avoid use of this product.

COMPANY IDENTITY: Hydro-Force Manufacturing
PRODUCT IDENTITY: VIPER GROUT & CONCRETE SEALER

SDS DATE: 03/29/2014
ORIGINAL: 03/29/2014

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

TARGET ORGANS: May cause damage to target organs, based on animal data.

IRRITANCY: Irritating to contaminated tissue.

SENSITIZATION: No component is known as a sensitizer.

MUTAGENICITY: No known reports of mutagenic effects in humans.

EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.

TERATOGENICITY: No known reports of teratogenic effects in humans.

REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

MAMMALIAN TOXICITY INFORMATION

No mammalian information is available on this product.

SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

EFFECT OF MATERIAL ON AQUATIC LIFE:

No aquatic environmental information is available on this product.

MOBILITY IN SOIL

Mobility of this material has not been determined.

DEGRADABILITY

This product is completely biodegradable.

ACCUMULATION

Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.

SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: No
DOT/TDG SHIP NAME: Not Regulated
DRUM LABEL: None
IATA / ICAO: Not Regulated
IMO / IMDG: Not Regulated
EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

COMPANY IDENTITY: Hydro-Force Manufacturing
PRODUCT IDENTITY: VIPER GROUT & CONCRETE SEALER

SDS DATE: 03/29/2014
ORIGINAL: 03/29/2014

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health

All components of this product are on the TSCA list.
This material contains no known products restricted under SARA Title III,
Section 313 in amounts greater or equal to 1%.



STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN
CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):
This product contains no chemicals known to the State of California
to cause cancer or reproductive toxicity.

INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories
of the following countries:
Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS),
Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),
Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled
Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 1, PHYSICAL HAZARD: 0
(Personal Protection Rating to be supplied by user based on use conditions.)
This information is intended solely for the use of individuals
trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware
of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 03/29/2014

NOTICE

Hydro-Force Manufacturing disclaims all expressed or implied warranties of merchantability or
fitness for a specific use, with respect to the product or the information provided herein,
except for conformation to contracted specifications. All information appearing herein
is based upon data obtained from manufacturers and/or recognized technical sources.
While the information is believed to be accurate, we make no representations as to its
accuracy or sufficiency.
Conditions of use are beyond our control, and therefore users are responsible for
verifying the data under their own operating conditions to determine whether the product
is suitable for their particular purposes and they assume all risks of their handling,
and disposal of the product. Users also assume all risks in regards to the publication
or use of, or reliance upon information contained herein.
This information relates only to the product designated herein, and does not relate to
its use in combination with any other material or process.