

1. Product and Company Identification

Product Code: FP6001
Product Name: Hard Rock Marble Polish
Company Name: Masterpiece Manufacturing, Inc.
P.O. Box 97818
Las Vegas, NV 89193-7818
Phone Number: (702)656-9767
Emergency Contact: Chemtrec (800)424-9300
Recommended Use: Polish
Intended Use: For sale to, use and storage by service persons only.

2. Hazards Identification

Acute Toxicity: Oral, Category 3

Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2A



GHS Signal Word: Danger

GHS Hazard Phrases: Toxic if swallowed.
Causes skin irritation.
Causes serious eye irritation.

GHS Precaution Phrases: Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Keep out of reach of children.
Wear protective gloves, protective clothing, eye protection, face protection.
Take off contaminated clothing and wash it before reuse.

GHS Response Phrases: IF SWALLOWED: Call a POISON CENTER or doctor/physician.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, get medical attention immediately.

GHS Storage and Disposal Phrases: Store in cool dry place at room temperature away from direct sunlight.
Dispose of contents and container according to the local, city, state and federal regulations.

Potential Health Effects (Acute and Chronic): Chronic: Chronic inhalation and ingestion may cause chronic fluoride poisoning (fluorosis) characterized by weight loss, weakness, anemia, brittle bones, and stiff joints. Effects may be delayed. Chronic exposure to fluoride compounds may cause systemic toxicity.

Inhalation: Causes chemical burns to the respiratory tract.

Skin Contact: Causes skin burns. May cause skin rash (in milder cases), and cold and clammy skin with cyanosis or pale color.

Eye Contact: Causes eye burns. May cause chemical conjunctivitis and corneal damage.

Ingestion: May cause severe and permanent damage to the digestive tract. Causes gastrointestinal tract burns. May cause perforation of the digestive tract.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
16949-65-8	Magnesium hexafluorosilicate	Proprietary
16961-83-4	Fluosilicic acid	Proprietary
73138-45-1	Fatty acids, montan-wax, ethylene esters	Proprietary

4. First Aid Measures

Emergency and First Aid**Procedures:**

In Case of Inhalation:	Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Do NOT use mouth-to-mouth resuscitation. If breathing has ceased apply artificial respiration using oxygen and a suitable mechanical device such as a bag and a mask.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes.
In Case of Eye Contact:	Get medical aid immediately. Do NOT allow victim to rub eyes or keep eyes closed. Extensive irrigation with water is required (at least 30 minutes).
In Case of Ingestion:	Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.
Note to Physician:	Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt:	NP	Method Used:	Estimate
Explosive Limits:	LEL: N/A	UEL:	N/A
Autoignition Pt:	NP		
Suitable Extinguishing Media:	Substance is noncombustible; use agent most appropriate to extinguish surrounding fire.		
Fire Fighting Instructions:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.		
Flammable Properties and Hazards:	No data available.		

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Provide ventilation.
---	---

7. Handling and Storage

Precautions To Be Taken in Handling:	Wash thoroughly after handling. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Do not get on skin or in eyes. Avoid ingestion and inhalation. Do not ingest or inhale. Discard contaminated shoes.
Precautions To Be Taken in Storing:	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Corrosives area. Avoid storage in glass containers.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
16949-65-8	Magnesium hexafluorosilicate	No data.	No data.	No data.
16961-83-4	Fluosilicic acid	No data.	No data.	No data.
73138-45-1	Fatty acids, montan-wax, ethylene esters	No data.	No data.	No data.

Respiratory Equipment (Specify Type): A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Opaque pink color liquid with minty odor.

Melting Point: NE

Boiling Point: > 212.00 F

Decomposition Temperature: NE

Autoignition Pt: NP

Flash Pt: NP Method Used: Estimate

Explosive Limits: LEL: N/A UEL: N/A

Specific Gravity (Water = 1): 1.100

Density: 9.174 LB/GA

Vapor Pressure (vs. Air or mm Hg): NE

Vapor Density (vs. Air = 1): NE

Evaporation Rate: NE

Solubility in Water: 100%

Saturated Vapor Concentration: NE

Viscosity: NP

pH: 0.5 - 2.0

Percent Volatile: No data.

VOC / Volume: 0.0000 G/L

10. Stability and Reactivity

Stability: Unstable [] Stable [X]
Conditions To Avoid - Incompatible materials.
Instability:
Incompatibility - Materials To Avoid: glass, Strong oxidizing agents.
Hazardous Decomposition Or Byproducts: irritating and toxic fumes and gases, hydrogen fluoride gas. silicon dioxide.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: None.

11. Toxicological Information

Toxicological Information: No data available.
Carcinogenicity/Other Information: CAS# 16961-83-4: Not listed by ACGIH, IARC, NTP, or CA Prop 65.
CAS# 7732-18-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65.
Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Dispose of contents and container according to the local, city, state and federal regulations.

14. Transport Information**LAND TRANSPORT (US DOT):**

DOT Proper Shipping Name: Quart and one gallon: Limited Quantity.
DOT Hazard Class: 6.1 POISON
UN/NA Number: UN2856 **Packing Group:** III

**LAND TRANSPORT (Canadian TDG):**

TDG Shipping Name: UN2856, Fluorosilicates, n.o.s., (Contains Magnesium Fluorosilicate), 6.1, III.

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: UN2856, Fluorosilicates, n.o.s., (Contains Magnesium Fluorosilicate), 6.1, III.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: UN2856, Fluorosilicates, n.o.s., (Contains Magnesium Fluorosilicate), 6.1, III.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
16949-65-8	Magnesium hexafluorosilicate	No	No	No
16961-83-4	Fluosilicic acid	No	No	No
73138-45-1	Fatty acids, montan-wax, ethylene esters	No	No	No

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists


16949-65-8	Magnesium hexafluorosilicate	CA PROP.65: No; CA TAC, Title 8: No
16961-83-4	Fluosilicic acid	CA PROP.65: No; CA TAC, Title 8: No
73138-45-1	Fatty acids, montan-wax, ethylene esters	CA PROP.65: No; CA TAC, Title 8: No

16. Other Information

Hazard Rating System:

HEALTH	3
FLAMMABILITY	0
PHYSICAL	0
PPE	C

HMIS:



Revision Date: 04/07/2015

Additional Information About This Product: No data available.

This Product:

Company Policy or

Disclaimer:

The manufacturer believes the data set forth are accurate and makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion.