Safety Data Sheet

1567BR



1 Material and Supplier Identification

Product Name: MAX-3X Liquid Presoak

Description: Silverware & Utensil Presoak #6

Recommended use of the Use only for the purpose on product label. This product is not intended to be used without

chemical and restrictions: prior dilution if specified on product label.

Supplier's Information: Brady Industries

7055 Lindell Rd Las Vegas, NV 89118

800-293-4698 (Customer Service)

Emergency Telephone: (800) 255-3924 USA (813)248-0585 International (Chemtel 24 hrs)

2 Hazards Identification

Classification of Mixture: Serious Eye Damage: Category 1 Pictogram

Signal Word: DANGER

Hazard Statements: Causes serious eye damage

Precautionary Statements

General: KEEP OUT OF REACH OF CHILDREN. Read label before use.

Prevention: Wash hands thoroughly after handling. Wear eye protection

Response:

IF IN EYES: Rinse cautiously with water for several minutes.Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical attention immediately.

3 Composition/Information on Ingredients

<u>Hazardous Ingredients</u> <u>CAS Number</u> <u>Concentration Range %</u>

 Alcohols, Ethoxylated
 68439-46-3
 5-15

 Protease
 9001-92-7
 1-5

3/10/2021 1567BR MAX-3X Liquid Presoak Page 1 of 5

4 First Aid Measures

Eye Contact: Flush eyes with water for 15 minutes. Remove contact lenses if any.

Skin Contact: Contact with concentrate may be an irritant to sensitive skin. If spilt in large areas of skin,

rinse immediately with water and remove clothing. Wash skin thoroughly with soap and

water.

Inhalation If discomfort is experienced after prolonged exposure to vapors, move person to fresh air.

Get medical attention if irritation persists.

Ingestion: Get medical attention immediately. Rinse mouth with water. Do NOT induce vomiting.

Drink glass of water to dilute product.

5 Firefighting Measures

Suitable Extinguishing Media: Water spray, normal foam, dry agent (carbon dioxide, dry chemical powder.)

Specific Hazards arising from

the Chemical:

In a fire or if heated, a pressure increase will occur and the container may burst. Combustion products may include and are not limited to nitrogen oxides, carbon

monoxide, and carbon dioxide.

Specific Protective Equipment and Precautions for Firefighters:

Firefighters should wear NIOSH approved self-contained breathing apparatus and protective clothing. If safe to do so, remove containers from path of fire. If involved in a

fire, keep containers cool with water spray.

6 Accidental Release Measures

Emergency Procedures: Keep area clear of personnel until area has been properly cleaned.

Personal Precautions/

Protective Equipment:

Slippery when spilt. To avoid accidents, clean up immediately and shut off source of leak, if safe to do so. Wear appropriate protective equipment to prevent any contamination of skip avec and paragraph alathing. Provide sufficient ventilation

skin, eyes, and personal clothing. Provide sufficient ventilation.

Environmental Precautions:

Methods for Containment and

Cleaning Up:

If contamination of sewers or waterways has occurred, advise local emergency services.

Contain spill with absorbent (soil, sand, or other inert material) or spill kit to prevent contamination of sewers or waterways. Neutralization agent is not recommended within building, as toxic vapors may be omitted. Properly dispose of used absorbents in

accordance with local, state, and federal regulations.

7 Handling and Storage

Precautions for Safe Handling: Avoid skin and eye contact, inhalation and ingestion. Wash hands thoroughly after use.

Keep out of reach of children.

Conditions for Safe Storage, Including Incompatibilities:

Store in cool, dry place and out of direct sunlight. Store away from source of heat or ignition. Do not mix with other chemicals. Keep container closed when not in use, and

check regularly for leaks.

See Section 10 for incompatible materials.

See Section 10 for incompatible materials.

3/10/2021 1567BR MAX-3X Liquid Presoak Page 2 of 5

8 Exposure Controls/Personal Protection

Control Parameters:

<u>Hazardous Ingredients</u> <u>ACGIH TLV</u> <u>OSHA PEL</u> <u>NIOSH IDLH</u>

Alcohols, Ethoxylated N/A N/A N/A
Protease N/A 6 mg/m3 N/A

Appropriate engineering

controls:

Good ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal Protection

Eye Protection: May use protective glasses if splashing or spray-back is likely.

Hand Protection: May use protective gloves (e.g., nitrile, vinyl) when used for prolong periods or if skin is

sensitive.

Skin Protection: No special protective equipment required.

Respiratory Protection: Use in well ventilated areas or local exhaust ventilation when cleaning small spaces.

Hygiene Measures: Always wash hands after handling chemical products, and before smoking, eating,

drinking, or using the toilet. Wash contaminated clothing or protective equipment before

storage and re-use.

9 Physical and Chemical Properties

Physical State: Liquid Specific Gravity: 1.009 Vapour Pressure (mm Hg): < 17 mm Hg

Color: **Evaporation Rate:** > 1 Green < 1 Vapour Density: Odor: None Solubility in Water: Complete Freezing Point (°F): < 32 No VOC 7-8 VOC (g/L): Boiling Point (°F): > 212 pH: Flash Point (°F): > 200

< means less than</p>
> means greater than

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

10 Stability and Reactivity

Reactivity: No specific data

Chemical Stability: Stable

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid exposure to heat and light.

Incompatible Materials: Slightly reactive or incompatible with oxidizers (e.g., bleach), strong acids (e.g.,

hydrochloric acid) and reactive metals (e.g., aluminum).

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

3/10/2021 1567BR MAX-3X Liquid Presoak Page 3 of 5

11 Toxological Information

Symptoms:

Eye Contact: Adverse symptoms may include the following: irritation, watering, redness

Skin Contact: Adverse symptoms may include the following: irritation, redness

Inhalation: Adverse symptoms may include the following: respiratory tract irritation, coughing

Ingestion: Adverse symptoms may include the following: stomach pains

Acute Toxicity:

Eye Contact: Causes eye irritation

Skin Contact: May cause skin irritation.

Inhalation: May cause respiratory irritation.

Ingestion: May cause burns to mouth, throat and stomach.

Toxicity Data:

<u>Hazardous Ingredients</u> <u>Result</u> <u>Species</u> <u>Dose</u>

Alcohols, Ethoxylated LD50-Oral Rat >2000 mg/kg

LD50 - Dermal Rabbit 20800 mg/kg

Protease No data available

Chronic Effects: No known significant effects or critical hazards

12 Ecological Information

Ecotoxicity: No data available.

Aquatic Toxicity:

<u>Hazardous Ingredients</u> <u>Result</u> <u>Species</u> <u>Dose</u>

Alcohols, Ethoxylated LC50 Fathead minnow (Pimephales Promelas) 8.5 mg/l/96

hrs

EC50 Daphnia 5.3 mg/l /48 hrs

Protease No data available

Other Adverse Effects: No known significant effects or critical hazards.

13 Disposal Considerations

Disposal Methods: Diluted product can be flushed to sanitary sewer. Discard empty container in trash.

Dispose of waste in accordance with federal, state, and local regulations.

14 Transportation Information

Certain shipping modes or package sizes may have exceptions from the transport regulations.

The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

Ground Transport

DOT Classification: Not Regulated

UN Number:

Transport Hazard Class: N/A
Packaging Group: N/A

Hazardous Division: Hazardous Contents:

15 Regulatory Information

SARA Title III: No California Proposition 65: No

3/10/2021 1567BR MAX-3X Liquid Presoak Page 4 of 5

Other Regulations:

16 Other Information

HMIS/NFPA Hazard Rating:

Health: 1

Flammability: 0

Reactivity: 0

The information contained herein is based on the data available to us. It is believed to be correct. NO warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult Brady Industries.

3/10/2021 1567BR MAX-3X Liquid Presoak Page 5 of 5