

SAFETY DATA SHEET

CON-DENSE LS	SDS Number : LS-615	Revision Date: 03/18/2024
---------------------	----------------------------	----------------------------------

1. PRODUCT AND COMPANY IDENTIFICATION:

Product Name: CON-DENSE LS

Product Code: LS-615

Product Use: Waterborne Silicate Concrete Densifier

Synonyms: Concrete Hardener

Chemical Formula: Mixture of substances listed below
with nonhazardous additions

Restrictions: Institutional, Commercial and Retail
Concrete Floor Use Only

Manufacturer:


SureTec Innovations
190 S McQueen Road
Gilbert, AZ 85233
888-767-4764
www.suretecinnovations.com

Emergency contact: Chemtrec 800.424.9300

CCN No. 21541

2. HAZARD IDENTIFICATION:

GHS CLASSIFICATION:

<u>HEALTH</u>	<u>ENVIRONMENTAL</u>	<u>PHYSICAL</u>
<i>Skin Corrosion/Irritation: Category 2</i> <i>Eye Damage/Irritation: Category 2</i>	<i>Acute Toxicity: None Known</i> <i>Chronic Toxicity: None Known</i>	<i>None</i>
	<u>Signal Word:</u> Warning	
<u>Hazard Statements</u> Causes skin irritation Causes eye irritation		
<u>Precautionary Statements</u> Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing mist or spray. IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs or persists: Get medical attention. IF ON SKIN: Remove immediately all contaminated clothing. Rinse skin with water for several minutes. If skin irritation occurs or persists: Get medical attention. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or physician. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a closed container. Dispose of contents/container in accordance with local regulation.		

SAFETY DATA SHEET

CON-DENSE LS**SDS Number : LS-615****Revision Date: 03/18/2024**

3. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENT	CAS NO.	PERCENT	HAZARDOUS
SILICIC ACID, LITHIUM SALT	12627-14-4	5 – 15%	YES
Exact Percentages are being withheld as trade secret information.			

4. FIRST-AID MEASURES:

Eye Contact: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs or persists: get medical attention.

Skin Contact: Remove immediately all contaminated clothing. Rinse with water for several minutes. If skin irritation occurs or persists: get medical attention. Wash contaminated clothing before reuse.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or physician.

5. FIRE-FIGHTING MEASURES:

Fire Extinguishing media: Use water spray, dry chemical, carbon dioxide or regular foam. Move containers away from fire area if it can be done without risk.

Hazards during fire-fighting:

Containers may rupture when exposed to extreme heat.

Protective equipment for fire-fighting:

Wear NFPA-approved self-contained breathing apparatus, helmet, hood, boots and gloves.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions:

Use recommended personal protective clothing and equipment. To prevent slipping, do not walk through spilled material.

Environmental precautions:

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off of work area, and material should be absorbed, collected and disposed of in accordance with regulations. Keep product from entering storm drains. Consult local and federal guidelines for proper disposal of these materials.

Cleanup:

- For small amounts of released material: Mop or vacuum up, or absorb with suitable material then transfer to container for disposal. - For large amounts of released material: Dike around spilled material with absorbent to contain. Spilled material may be mopped or vacuumed up, or absorbed, then transferred to plastic containers for disposal.

SAFETY DATA SHEET

CON-DENSE LS	SDS Number : LS-615	Revision Date: 03/18/2024
---------------------	----------------------------	----------------------------------

7. HANDLING and STORAGE:

Handling:

General advice - No specific measures are necessary provided product and recommended protective clothing/equipment are used correctly. Do not mix with other chemicals. This is a commercial product, not intended for home use. Keep out of reach of children.

Storage:

General advice - Protect against physical damage. Store in tightly closed containers in a cool, well ventilated area. Do not allow product to freeze.

Shelf Life:

12 months

8. EXPOSURE CONTROLS and PERSONAL PROTECTION:

Advice on system design:

Provide local exhaust ventilation to control vapors for published exposure limits.

Personal protective equipment (HMIS rating 'B'):

Eye protection: Wear safety glasses with side shields or safety goggles to prevent exposure or full face shield if splash hazard exists.

Skin protection: Chemical-resistant gloves. Wear appropriate protective clothing to prevent possible skin contact.

Respiratory protection: Not normally required. Avoid breathing mists or spray. Use proper NIOSH-OSHA respirator if ventilation is inadequate.

General safety and hygiene measures: Exercise stringent hygiene practices to minimize exposure. If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking or smoking.

Other protective measures:

Nearby running water on the job site is necessary, should an accident occur.

Exposure Guidelines:

None

9. PHYSICAL and CHEMICAL PROPERTIES:

Appearance:	Clear Colorless Liquid	Flash Point:	None
Odor:	None	Upper/Lower Flammability Limits:	No information available
pH value:	11.2+/- 0.2	Relative Density (water):	1.08
		Auto-Ignition Temperature:	No information available
		Decomposition temperature:	No information available
Specific gravity:	1.08 (H2O = 1)	Partition Coefficient	No information available
Solidification temperature:	No information available	Odor Threshold	No information available
Freezing/Melting point:	No information available	Viscosity:	< 10 cps.
Boiling point:	212°F (100 °C)	Partition Coefficient	No information available
Vapor density:	No information available	Solubility in water:	100%
Vapor pressure:	No information available		
Evaporation Rate:	No information available		
Regulatory VOC:	<1 g/l		

SAFETY DATA SHEET

CON-DENSE LS

SDS Number : LS-615

Revision Date: 03/18/2024

10. STABILITY and REACTIVITY:

Conditions to avoid: Excessive heat or flame.

Substances to avoid: Strong oxidizing agents, acids and bases.

Hazardous reactions: Product is chemically stable under normal conditions of use and storage.

Decomposition or By-products: None

11. TOXICOLOGY INFORMATION:

Acute Toxicity (Symptoms):

Oral Ingestion may cause mouth and throat irritation due to alkalinity, nausea, vomiting, and diarrhea. Ingestion of large amounts of lithium compounds may cause central nervous system damage and kidney damage.

Eye irritation: Irritation, redness and tearing.

Skin irritation: Irritation and redness.

Inhalation: Irritation to the respiratory tract, headache and dizziness.

Sensitization: Skin: N/A. Respiratory: N/A

Chronic Toxicity:

Other information: No carcinogenic substances as defined by ACGIH, IARC, NTP and/or OSHA.

12. ECOLOGICAL INFORMATION:

Biodegradation:

Test method: Unspecified

Analysis method: Unspecified

Degree of elimination: Not Established

Environmental toxicity:

Acute and prolonged toxicity to fish: Not Established

Toxicity to microorganisms: Not Established

Other ecotoxicological advice: Not Established

13. DISPOSAL CONSIDERATIONS:

Waste disposal of substance: Dispose of in accordance with all Federal, State and Local regulations when storing and disposing of substances. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA (EPA regulations for hazardous waste).

Container disposal: Dispose of in a licensed facility in accordance with local regulations.

RCRA:

Unspecified.

14. TRANSPORTATION INFORMATION:

DOT:

Proper Shipping Name: CEMENT WATERPROOFING COMPOUND (NON-HAZARDOUS)

SAFETY DATA SHEET

CON-DENSE LS

SDS Number : LS-615

Revision Date: 03/18/2024

15. REGULATORY INFORMATION:

Federal Regulations:**Registration status:**

TSCA, US:

All components are listed or exempt.

SARA hazard category (EPCRA 311/312):

Acute health hazard

SARA TITLE III, SECTION 313:

CAS Number: _____ Chemical Name: _____

None

State Regulations:

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

CAS Number: _____ Chemical Name: _____

None

16. OTHER INFORMATION:

NFPA Rating:

Health: 1

Fire: 0

Reactivity: 0

Special Hazard: none

HMIS III Rating:

Health: 1


Flammability: 0

Physical Hazard: 0

Personal Protection: B (safety glasses with side shields and chemical-resistant gloves)

Both NFPA and HMIS III rating systems use a numbering scale that ranges from 0 to 4 to indicate the degree of hazard. A value of zero means the substance possesses no hazard while a value of four indicates high hazard.

NFPA Rating



HMIS Rating

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

Prepared by: SureTec Innovations 03/18/2024 **Revision No.:** 1**Local Contact Information:**

SureTec Innovations

190 S McQueen Road

Gilbert, AZ 85233

888-767-4764

www.suretecinnovations.com

Notice: The information provided is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

Warranty: This is a proprietary SureTec product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact SureTec with any questions regarding this policy.