

2053 LYNX STAINLESS STEEL CLEANER & POLISH

SECTION 1: Identification

Trade Name: 2053 LYNX STAINLESS STEEL CLEANER & POLISH 04/19/2018 Date Prepared: Product Identification: 6524 Additional ID: LX-2053

Synonyms: Solvent blend

Product Use Description: Metal Cleaner

Manufactured By:

ABC COMPOUNDING CO., INC.

PO BOX 80729

Convers, GA 30013 US

Phone: (800) 795-9222 Website: www.lynxclean.com

(800) 535-5053 24 HR Emergency Number:

SECTION 2: Hazards Identification

Classifications

Flammable liquids - Category 3

Aspiration Hazard - Category 1

Eye Irritation - Category 2

Skin Irritation - Category 2

Skin Sensitization - Category 1

Specific Target Organ Toxicity (single exposure) - Category 3







Irritant

Heatlh Hazard

Signal Word:

Danger

Hazard Statements

Keep out of reach of children. Read label and SDS before use.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes skin and serious eye irritation.

May cause an allergic skin reaction.

Flammable liquid and vapor.

Precautionary Statements

Prevention

Avoid breathing mist/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye or face protection.

Contaminated clothing must not be allowed out of the workplace.

Trade Name: 2053 LYNX STAINLESS STEEL CLEANER & Product ID: 652432PL Page 1 of 6 **SPS**| **FD**! SDS05503 Revision #: 2 **Revision Date: 04/19/2018**

2053 LYNX STAINLESS STEEL CLEANER & POLISH

Keep away from heat, sparks, open flames and hot surfaces. □ -No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/handling/process quipment.

Use only non-sparking tools. Take precautionary measures against static discharge.

Response

IF SWALLOWED: Immediately call a poison center. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs get medical attention.

Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or a doctor if you feel unwell.

IN CASE OF FIRE: Use carbon dioxide, foam or dry chemical to extinguish.

Storage

Store locked up in a well-ventilated place.

Keep cool.

Keep container tightly closed.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

SECTION 3: Composition

Observation	Concentration % by	
Chemical Name	CAS#	Weight
Hydrotreated Heavy Naphthenic Distillate	64742-52-5	40 - 60
D-limonene	5989-27-5	20 - 40
Aliphatic Hydrocarbons	64742-47-8	10 - 30

SECTION 4: First Aid Measures

EMERGENCY OVERVIEW

DANGER. Flammable/combustible liquid. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

SECTION 5: Firefighting Measures

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Runoff to sewer may create fire hazard.

 Trade Name: 2053 LYNX STAINLESS STEEL CLEANER &
 Product ID: 652432PL
 Page 2 of 6

 Revision #: 2
 Revision Date: 04/19/2018

2053 LYNX STAINLESS STEEL CLEANER & POLISH

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

SECTION 6: Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. **DO NOT use clay-type absorbent materials.** Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

SECTION 7: Handling and Storage

Do not get in eyes, on skin or on clothing. Avoid breathing sprays and vapors. Avoid skin contact. Keep out of reach of children.

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Ground/bond container and receiving equipment. Use explosion-proof ventilating and equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

SECTION 8: Exposure Controls/Personal Protection

Aliphatic Hydrocarbons(64742-47-8)				
OSHA PEL	300 ppm			
Hydrotreated Heavy Naphthenic Distillate(64742-52-5)				
OSHA PEL	5 mg/m3			
ACGIH TLV	5 mg/m3			

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2requirements must be followed.

Engineering Controls: Good general ventilation required.

SECTION 9: Physical and Chemical Properties

Trade Name: 2053 LYNX STAINLESS STEEL CLEANER & Product ID: 652432PL Page 3 of 6

Self-12 SDS05503 Revision #: 2 Revision Date: 04/19/2018

2053 LYNX STAINLESS STEEL CLEANER & POLISH

Property	Value	Property	Value
Appearance	CLEAR LIQUID	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Color	COLORLESS
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	122 F	Melting/Freezing Point	NOT AVAILABLE
Odor	CITRUS	Odor Threshold	NOT AVAILABLE
Other Information	VOC content (wt. %): 50	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID
Relative Density	0.8	Solubility (Water)	INSOLUBLE
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE
Viscosity	NOT AVAILABLE	pH	NOT APPLICABLE

SECTION 10: Stability and Reactivity

Reactivity

Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability

Stable under normal conditions.

Incompatible Materials

Acids, strong oxidizers, inorganic clays (clay-type absorbents)

Conditions to Avoid

High temperatures, open flames, sparks, welding.

Hazardous Decomposition Products

CO, CO2

Vapors may ignite at temperatures exceeding flash point.

SECTION 11: Toxicological Information

Primary Route of Entry: Skin contact, inhalation, ingestion

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin and cause sensitization. Symptoms may include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system.

Reproductive/Developmental Information: Not available.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Not available.

Trade Name: 2053 LYNX STAINLESS STEEL CLEANER &Product ID: 652432PLPage 4 of 6SDS 101: SDS 05503Revision #: 2Revision Date: 04/19/2018

2053 LYNX STAINLESS STEEL CLEANER & POLISH

SECTION 12: Ecological Information

Not available.

SECTION 13: Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

SECTION 14: Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 2319

Proper shipping name TERPENE HYDROCARBONS MIXTURE, N.O.S. (CONTAINS D'LIMONENE)

Class 3

Packing group III

NOT REGULATED FOR NON-BULK GROUND DOMESTIC SHIPMENTS

SECTION 15: Regulatory Information

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure () Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status:</u> Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D001

SECTION 16: Other Information

HMIS Ratings:



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

 Trade Name: 2053 LYNX STAINLESS STEEL CLEANER &
 Product ID: 652432PL
 Page 5 of 6

 Revision #: 2
 Revision Date: 04/19/2018

2053 LYNX STAINLESS STEEL CLEANER & POLISH

Preparation/Revision Date: 04/19/2018

 Trade Name: 2053 LYNX STAINLESS STEEL CLEANER &
 Product ID: 652432PL
 Page 6 of 6

 SOS 161: SDS 05503
 Revision #: 2
 Revision Date: 04/19/2018