

DuPont(TM) StoneTech(R) Professional Sealer

6457CR

Revised 4-OCT-2007

Substance ID :130000027556

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont StoneTech(R) Professional 370 North Wiget Lane, Suite 200 Walnut Creek, CA 94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000

Transport Emergency : CHEMTREC: 800-424-9300/Outside US:

703-527-3887

Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

-----

# Components

Material CAS Number %

Dipropylene Glycol n-Butyl Ether 29911-28-2

Mixed Fluoroalkyl Salts

Water 7732-18-5 >70

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation may cause respiratory irritation. Inhalation of large amounts of respirable particles may be toxic to the lungs.

Eye contact may cause eye irritation with discomfort, tearing, or blurring of vision.

Skin contact may cause skin irritation with discomfort or rash.

Ingestion may cause nausea and vomiting. Repeated ingestion of large amounts may cause liver damage.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES \_\_\_\_\_\_ First Aid

# INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

#### SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing

#### EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

### INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

\_\_\_\_\_ \_\_\_\_\_\_

### FIRE FIGHTING MEASURES

Flammable Properties

Non-flammable.

Extinguishing Media

Water, Foam, Dry Chemical, CO2.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

#### ACCIDENTAL RELEASE MEASURES

\_\_\_\_\_

Safequards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material. Shovel or sweep up.

-----

#### HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures.

#### EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Keep container tightly closed. Use only with adequate ventilation. Vent heated extruder or dryer fumes outside work area. Do not aerosolize. In spray applications, use airless type pressure spray equipment at less than 60 psi, and exhaust ducts, drip pans, or other design features to minimize worker exposure to mists and overspray.

~\_\_\_\_\_

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

Dipropylene Glycol n-Butyl Ether AEL \* (DuPont) : 50 ppm, 8 & 12 Hr. TWA \* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence. PHYSICAL AND CHEMICAL PROPERTIES Physical Data Solubility in Water : Soluble : 8-9 рН Odor : (mild), Sweet. Form : Liquid. : (light), Amber. Color Specific Gravity \_\_\_\_\_\_ STABILITY AND REACTIVITY Chemical Stability Stable. Incompatibility with Other Materials Incompatible with strong alkaline compounds, acids and oxidizing agents. Decomposition Thermal decomposition may produce carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen fluoride and acrid smoke. Polymerization Polymerization will not occur. DISPOSAL CONSIDERATIONS Waste Disposal Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations. TRANSPORTATION INFORMATION Shipping Information

Not Regulated as a hazardous material by DOT, IMO, or IATA.
REGULATORY INFORMATION
U.S. Federal Regulations
TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.
$VOC = <400 \ g/L$ excluding water; 12 g/L including water (Low Solids Coating)

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

# Indicates updated section.

End of MSDS