

1. Product and Company Identification

Product Code: 06454
Product Name: Paint, Oil & Grease Remover
Company Name: Genlabs **Phone Number:**
 5568 Schaefer Ave. 1 (909)591-8451
 Chino, CA 91710
Web site address: www.genlabscorp.com
Emergency Contact: Chemtrec 1 (800)424-9300

Recommended Use: Paint Oil & Grease Remover
Intended Use: For sale to, use and storage by service persons only.

2. Hazards Identification

Aspiration Toxicity, Category 1
Flammable Liquids, Category 4
Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 5
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2
Acute Toxicity: Inhalation, Category 4



GHS Signal Word: **Danger**

GHS Hazard Phrases: May be fatal if swallowed and enters airways.
 Combustible liquid.
 Harmful if swallowed.
 May be harmful in contact with skin.
 Causes skin irritation.
 Causes serious eye irritation.
 Harmful if inhaled.

GHS Precaution Phrases: Wear protective gloves, protective clothing, eye protection, face protection.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Take off contaminated clothing and wash it before reuse.
 Keep out of reach of children.

GHS Response Phrases: If swallowed: Immediately call a Poison Center or doctor. Do NOT induce vomiting.
 Rinse mouth.
 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 If on skin (or in hair): Wash with plenty of soap and water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists, get medical attention immediately.

GHS Storage and Disposal Phrases: Store in cool dry place at room temperature away from direct sunlight.
 Dispose of contents and container according to the local, city, state and federal regulations.

Potential Health Effects (Acute and Chronic): Prolonged or repeated skin contact may cause defatting and dermatitis.

Inhalation: Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung damage. May cause anemia. May cause central nervous system effects such as nausea and headache.

Skin Contact: May cause irritation with burning pain, itching and redness. Harmful if absorbed through the skin. Causes skin irritation.

Eye Contact: Causes eye irritation. May cause transient corneal injury. Causes redness and pain.

Ingestion: Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	Proprietary
64741-65-7	Alkylation naphtha, heavy	Proprietary
112-34-5	Diethylene glycol monobutyl ether	Proprietary
111-76-2	Ethanol, 2-Butoxy-	Proprietary

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathed in, move person into fresh air. Consult a physician.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists.

In Case of Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical aid.

In Case of Ingestion: Potential for aspiration if swallowed. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Do NOT induce vomiting. Consult a physician. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Call a poison control center.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: > 200.00 F Method Used: Cleveland Closed Cup

Explosive Limits: LEL: N/A UEL: N/A

Autoignition Pt: NE

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool.

Flammable Properties and Hazards: CONDITIONS OF FLAMMABILITY:
Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition.

7. Handling and Storage

Precautions To Be Taken in Handling: Wash thoroughly after handling. Use with adequate ventilation. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat and flame. Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Keep away from heat and sources of ignition. Use spark-proof tools and explosion proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from heat, sparks and flame. Do not ingest or inhale.

Precautions To Be Taken in Storing: Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in original container.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.
64741-65-7	Alkylation naphtha, heavy	No data.	No data.	No data.
112-34-5	Diethylene glycol monobutyl ether	No data.	No data.	No data.
111-76-2	Ethanol, 2-Butoxy-	PEL: 50 ppm	TLV: 20 ppm	No data.

Respiratory Equipment (Specify Type): Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Handle with gloves.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use adequate ventilation to keep airborne concentrations low. Use explosion-proof ventilation equipment.

Work/Hygienic/Maintenance Practices: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Amber colored liquid with solvent fragrance.
Melting Point: NE
Boiling Point: > 300.00 F
Decomposition Temperature: NE
Autoignition Pt: NE
Flash Pt: > 200.00 F Method Used: Cleveland Closed Cup
Explosive Limits: LEL: N/A UEL: N/A
Specific Gravity (Water = 1): 0.820
Density: 6.838 LB/GA
Vapor Pressure (vs. Air or mm Hg): NE
Vapor Density (vs. Air = 1): NE
Evaporation Rate: NE
Solubility in Water: Insoluble
Saturated Vapor Concentration: NE
Viscosity: NP
pH: NP
Percent Volatile: No data.
VOC / Volume: 24.6000 G/L

10. Stability and Reactivity

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: ignition sources, Heat, flames and sparks. Excess heat, Incompatible materials.
Incompatibility - Materials To Avoid: Strong oxidizing agents, Alkali metals, Powdered metals, Metals, Copper, Amines, Reducing agents, Organic materials, Alcohols, Peroxides, permanganates, potassium permanganate, acids, Aluminum, metal oxides. Soluble carbonates and phosphates, Hydroxides.
Hazardous Decomposition Or Byproducts: Nitrogen oxides, Carbon monoxide, oxides of sulfur, formed under fire conditions. Carbon oxides.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: None.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
64741-65-7	Alkylation naphtha, heavy	No	No	No
112-34-5	Diethylene glycol monobutyl ether	No	No	Yes-Cat. N230
111-76-2	Ethanol, 2-Butoxy-	No	No	Yes-Cat. N230


CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CA PROP.65: No; CA TAC, Title 8: No
64741-65-7	Alkylation naphtha, heavy	CA PROP.65: No; CA TAC, Title 8: No
112-34-5	Diethylene glycol monobutyl ether	CA PROP.65: No; CA TAC, Title 8: TAC
111-76-2	Ethanol, 2-Butoxy-	CA PROP.65: No; CA TAC, Title 8: TAC, Title 8

16. Other Information

Hazard Rating System:

HEALTH	2
FLAMMABILITY	1
PHYSICAL	0
PPE	G

HMIS:



Revision Date:

04/28/2015

Additional Information About This Product: No data available.

Company Policy or Disclaimer:

The manufacturer believes the data set forth are accurate and makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion.