



# Safety Data Sheet

## Spartan Chemical Company, Inc.

Revision Date: 23-Mar-2015

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identifier

**Product Name:** AQUASPORT WOOD FLOOR CLEANER  
**Product Number:** 5837  
**Recommended Use:** Cleaning agent  
**Uses Advised Against:** For Industrial and Institutional Use Only

**Manufacturer/Supplier:** Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, Ohio 43537 USA  
800-537-8990 (Business hours)  
[www.spartanchemical.com](http://www.spartanchemical.com)

#### **24 Hour Emergency Phone Numbers:**

**Medical Emergency/Information:** 888-314-6171  
**Transportation/Spill/Leak:** CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

#### **GHS Classification**

Serious Eye Damage/Eye Irritation: Category 2A  
Flammable Liquids: Category 3

#### **GHS Label Elements**

**Signal Word:**

**Symbols:**

#### **Warning**



**Hazard Statements:**

Causes serious eye irritation  
Flammable liquid and vapor.

**Precautionary Statements:**

**Prevention:**

Wash hands and any exposed skin thoroughly after handling.  
Wear eye / face protection  
Wear protective gloves  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground container and receiving equipment.  
Use explosion-proof electrical equipment.  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Response:**

**-Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**-Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**-Specific Treatment:**

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

**Fire:**

Water spray, fog or alcohol-resistant foam, Carbon dioxide, for extinction

<b>Storage:</b>	Store in a well-ventilated place. Keep cool
<b>Disposal:</b>	Dispose of contents and container in accordance with local, state and federal regulations.
<b>Hazards Not Otherwise Classified:</b>	Not Applicable
<b>Other Information:</b>	<ul style="list-style-type: none"> <li>• Harmful if swallowed</li> <li>• Causes mild skin irritation.</li> <li>• Inhalation of vapors or mist may cause respiratory irritation.</li> <li>• Keep out of reach of children.</li> </ul>

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
isopropanol	67-63-0	10-30
propylene glycol monomethyl ether	107-98-2	5-10

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

<b>-Eye Contact:</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>-Skin Contact:</b>	Wash with soap and water. If skin irritation occurs: Get medical attention.
<b>-Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
<b>-Ingestion:</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.
<b>Note to Physicians:</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Water spray (fog), Alcohol resistant foam, Carbon dioxide, Move containers from fire area if you can do it without risk
<b>Specific Hazards Arising from the Chemical:</b>	Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
<b>Hazardous Combustion Products:</b>	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
<b>Protective Equipment and Precautions for Firefighters:</b>	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Remove all sources of ignition. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
<b>Environmental Precautions:</b>	Do not rinse spill onto the ground, into storm sewers or bodies of water.
<b>Methods for Clean-Up:</b>	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

### 7. HANDLING AND STORAGE

<b>Advice on Safe Handling:</b>	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.
<b>Storage Conditions:</b>	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
propylene glycol monomethyl ether 107-98-2	STEL: 150 ppm TWA: 100 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>

### Engineering Controls:

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

### Personal Protective Equipment

#### Eye/Face Protection:

Wear splash goggles.

#### Skin and Body Protection:

Wear rubber or other chemical-resistant gloves.

#### Respiratory Protection:

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

### General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Light green
Odor:	solvent
pH:	9.0-10.0
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	84 °C / 183 °F
Flash Point:	36 °C / 97 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	0.97
Solubility(ies):	Soluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

## 10. STABILITY AND REACTIVITY

### Reactivity:

This material is considered to be non-reactive under normal conditions of use.

### Chemical Stability:

Stable under normal conditions.

### Possibility of Hazardous Reactions:

Not expected to occur with normal handling and storage.

### Conditions to Avoid:

Extremes of temperature and direct sunlight.

### Incompatible Materials:

Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products:** May include carbon monoxide, carbon dioxide (CO<sub>2</sub>) and other toxic gases or vapors.

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.  
**Symptoms of Exposure:**  
**-Eye Contact:** Pain, redness, swelling of the conjunctiva and blurred vision.  
**-Skin Contact:** Drying of the skin.  
**-Inhalation:** Nasal discomfort and coughing.  
**-Ingestion:** Pain, nausea, vomiting and diarrhea.  
**Immediate, Delayed, Chronic Effects**  
**Product Information:** Data not available or insufficient for classification.  
**Target Organ Effects:** Central nervous system. -Eyes. Respiratory System. -Skin.

### Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 19214 mg/kg  
 ATEmix (dermal): 53657 mg/kg  
 ATEmix (inhalation-dust/mist): 428.3 mg/l

### Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg ( Rat )	Not Available	Not Available
isopropanol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h
propylene glycol monomethyl ether 107-98-2	= 5200 mg/kg ( Rat )	= 13000 mg/kg ( Rabbit )	= 54.6 mg/L ( Rat ) 4 h > 24 mg/L ( Rat ) 1 h

**Carcinogenicity:** No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
isopropanol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50	Not Available	13299: 48 h <i>Daphnia magna</i> mg/L EC50
propylene glycol monomethyl ether 107-98-2	Not Available	20.8: 96 h <i>Pimephales promelas</i> g/L LC50 static 4600 - 10000: 96 h <i>Leuciscus idus</i> mg/L LC50 static	Not Available	23300: 48 h <i>Daphnia magna</i> mg/L EC50

**Persistence and Degradability:** No information available.

**Bioaccumulation:** No information available.

**Other Adverse Effects:** No information available.

## 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.  
**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations.  
**US EPA Waste Number:** D001

## 14. TRANSPORT INFORMATION

**DOT:**

**UN/ID No:** UN1993  
**Proper Shipping Name:** Flammable liquids, n.o.s., (contains isopropanol)  
**Hazard Class:** 3  
**Packing Group:** III  
**Special Provisions:** Gallon containers of this product meet the exception requirements of section 49 CFR 173.306 as a limited quantity and may be shipped as a limited quantity.

## 15. REGULATORY INFORMATION

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA 313**

This product contains the following listed substances:

**isopropanol**

CAS No 67-63-0 only if manufactured by the strong acid process, no supplier notification

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard:</b>	Yes
<b>Chronic Health Hazard:</b>	No
<b>Fire Hazard:</b>	Yes
<b>Sudden release of pressure hazard:</b>	No
<b>Reactive Hazard:</b>	No

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
acetaldehyde - 75-07-0	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

## 16. OTHER INFORMATION

<b>NFPA</b>	<b>Health Hazards:</b> 2	<b>Flammability:</b> 3	<b>Instability:</b> 0	<b>Special:</b> N/A
<b>HMIS</b>	<b>Health Hazards:</b> 2	<b>Flammability:</b> 3	<b>Physical Hazards:</b> 0	

**Revision Date:** 23-Mar-2015  
**Reasons for Revision:** No information available.

**Disclaimer:**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**