SAFETY DATA SHEET



Citrufoam

Section 1. Identification

GHS product identifier : Citrufoam

Product code 066

Other means of identification

: Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
General/Multi-Purpose Cleaner	
Uses advised against	Reason
For Industrial and Institutional Use Only	-

: Betco Corporation Supplier's details

400 Van Camp Road

Bowling Green, Ohio 43402

www.betco.com 888-462-3826

Emergency telephone number (with hours of operation)

: Chemtrec (800) 424-9300

24 hour

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SKIN SENSITIZATION - Category 1 **CARCINOGENICITY - Category 2**

GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements : Extremely flammable aerosol.

May cause an allergic skin reaction.

Suspected of causing cancer.

Toxic to aquatic life.

Precautionary statements

Section 2. Hazards identification

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection: Recommended: safety glasses with side-shields. Wear protective clothing: Recommended: Chemical Resistant Gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace. Pressurized container: Do not pierce or burn, even after use.

Response

: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

Storage

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise

: None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Not available.

: Mixture

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	≤10	64742-47-8
Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)	≤10	68603-38-3
(R)-p-mentha-1,8-diene	≤5	5989-27-5
propane	≤5	74-98-6
Terpenes and Terpenoids, sweet orange-oil	≤5	68647-72-3
sodium N-lauroylsarcosinate	≤5	137-16-6
butane	≤5	106-97-8
2,2'-iminodiethanol	≤3	111-42-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 2/15

Section 4. First aid measures

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

None known.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 3/15

Section 5. Fire-fighting measures

Specific hazards arising from the chemical

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

metal oxide/oxides

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 4/15

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light	ACGIH TLV (United States, 3/2018).
	Absorbed through skin.
	TWA: 200 mg/m³, (as total hydrocarbon
	vapor) 8 hours.
Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)	None.
(R)-p-mentha-1,8-diene	AIHA WEEL (United States, 7/2018). TWA: 30 ppm 8 hours.
propane	OSHA PEL 1989 (United States, 3/1989).
proparie	TWA: 1000 ppm 8 hours.
	TWA: 1800 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 1000 ppm 10 hours.
	TWA: 1800 mg/m³ 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 1000 ppm 8 hours.
	TWA: 1800 mg/m³ 8 hours.
	ACGIH TLV (United States, 3/2018). Oxygen
	Depletion [Asphyxiant]. Explosive potential.
Terpenes and Terpenoids, sweet orange-oil	None.
sodium N-lauroylsarcosinate	None.
2,2'-iminodiethanol	OSHA PEL 1989 (United States, 3/1989).
	TWA: 3 ppm 8 hours.
	TWA: 15 mg/m³ 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 3 ppm 10 hours.
	TWA: 15 mg/m³ 10 hours.

Date of issue/Date of revision : 2/4/2021 : 8/24/2020 Date of previous issue Version

Section 8. Exposure controls/personal protection

ACGIH TLV (United States, 3/2018). Absorbed through skin.

TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction and vapor

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields. Recommended: safety glasses with side-shields

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Chemical Resistant Gloves

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 6/15

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Aerosol. Compressed gas.]

Color : White. [Light]

Odor : Fruity.

Odor threshold : Not available.
pH : 9.5 to 10.5
Melting point : Not available.
Boiling point : Not available.

Flash point : Open cup: -104.4°C (-155.9°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 0.937

Solubility : Easily soluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Aerosol product

Type of aerosol : Foam
Heat of combustion : 4.14 kJ/g

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials: Not available.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 7/15

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(R)-p-mentha-1,8-diene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	4400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
(R)-p-mentha-1,8-diene	Skin - Mild irritant	Rabbit	-	24 hours 10 Percent	-
2,2'-iminodiethanol	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	5500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	50 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
(R)-p-mentha-1,8-diene	-	3	-
2,2'-iminodiethanol	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)	Category 3		Respiratory tract irritation
propane	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
2,2'-iminodiethanol	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Section 11. Toxicological information

Information on the likely routes of exposure

: Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 9/15

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
(R)-p-mentha-1,8-diene	Acute EC50 421 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 688 μg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
2,2'-iminodiethanol	Acute EC50 12 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute LC50 28800 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 2150 µg/l Fresh water Acute LC50 775 mg/l Fresh water	Daphnia - Daphnia pulex Fish - Lepomis macrochirus	48 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(R)-p-mentha-1,8-diene	4.38	-	high
propane	1.09	-	low
2,2'-iminodiethanol	-1.43	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 10/15

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN1950	UN1950	UN1950	Not available.	UN1950	UN1950
UN proper shipping name	Aerosol, Flammable	Aerosol, Flammable (butane, Distillates (petroleum), hydrotreated light)	Aerosol, Flammable	Not available (butane, Distillates (petroleum), hydrotreated light)	Aerosol, Flammable	Aerosol, Flammable (butane, Distillates (petroleum), hydrotreated light)
Transport hazard class(es)	2.1	2.1	2.1	2	2.1	2.1
Packing group	II	II	II	-	II	II
Environmental hazards	No.	No.	No.	No.	No.	No.

Additional information

DOT Classification : Reportable quantity 10000 lbs / 4540 kg [1280 gal / 4845.3 L]. Package sizes shipped

in quantities less than the product reportable quantity are not subject to the RQ

(reportable quantity) transportation requirements.

Limited quantity Yes.

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.13-2.17 (Class 2).

Explosive Limit and Limited Quantity Index 5

IMDG : Limited quantity Yes.

IATA : Limited quantity Yes.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available. to Annex II of MARPOL and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Commerce control list precursor: 2,2',2"-nitrilotriethanol

Clean Water Act (CWA) 307: diethyl phthalate

Clean Water Act (CWA) 311: sodium dodecylbenzenesulfonate; ammonia Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Date of issue/Date of revision : 2/4/2021 : 8/24/2020 Version : 2 11/15 Date of previous issue

Section 15. Regulatory information

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE AEROSOLS - Category 1

GASES UNDER PRESSURE - Compressed gas

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification	
Distillates (petroleum),	≤10	FLAMMABLE LIQUIDS - Category 4	
hydrotreated light		ASPIRATION HAZARD - Category 1	
butane	≤10	FLAMMABLE GASES - Category 1	
		GASES UNDER PRESSURE - Liquefied gas	
Amides, C16-18 and	≤10	SKIN IRRITATION - Category 2	
C18-unsatd., N,N-bis		SERIOUS EYE DAMAGE - Category 1	
(hydroxyethyl)		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)	
		(Respiratory tract irritation) - Category 3	
(R)-p-mentha-1,8-diene	≤5	FLAMMABLE LIQUIDS - Category 3	
		SKIN IRRITATION - Category 2	
		SKIN SENSITIZATION - Category 1	
propane	≤5	FLAMMABLE GASES - Category 1	
		GASES UNDER PRESSURE - Liquefied gas	
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)	
		(Respiratory tract irritation) - Category 3	
Terpenes and Terpenoids,	≤5	FLAMMABLE LIQUIDS - Category 3	
sweet orange-oil		ACUTE TOXICITY (oral) - Category 4	
		ACUTE TOXICITY (dermal) - Category 2	
		SKIN IRRITATION - Category 2	
		EYE IRRITATION - Category 2A	
	_	SKIN SENSITIZATION - Category 1B	
sodium N-lauroylsarcosinate	≤5	ACUTE TOXICITY (inhalation) - Category 2	
		SKIN IRRITATION - Category 2	
		SERIOUS EYE DAMAGE - Category 1	
2,2'-iminodiethanol	≤3	ACUTE TOXICITY (oral) - Category 4	
		SKIN IRRITATION - Category 2	
		SERIOUS EYE DAMAGE - Category 1	
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED	
		EXPOSURE) - Category 2	

SARA 313

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	2,2'-iminodiethanol	111-42-2	≤3
Supplier notification	2,2'-iminodiethanol	111-42-2	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: BUTANE; PROPANE; DIETHANOLAMINE

New York : The following components are listed: Diethanolamine

: The following components are listed: BUTANE; PROPANE; DIETHANOLAMINE; **New Jersey**

ETHANOL, 2,2'-IMINOBIS-

Pennsylvania : The following components are listed: BUTANE; PROPANE; ETHANOL, 2,2'-IMINOBIS-

California Prop. 65



MARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

	No significant risk level	Maximum acceptable dosage level
Diethanolamine	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Triethanolamine	Schedule III	Listed

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted. Canada : All components are listed or exempted. China : All components are listed or exempted.

Europe : Not determined.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined

New Zealand : All components are listed or exempted.

Philippines Not determined.

Republic of Korea All components are listed or exempted. **Taiwan** : All components are listed or exempted.

Section 15. Regulatory information

Thailand : Not determined.


Turkey : Not determined.

United States : All components are listed or exempted.

Viet Nam : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
GASES UNDER PRESSURE - Compressed gas SKIN SENSITIZATION - Category 1	Expert judgment On basis of test data Expert judgment Expert judgment

History

Date of printing : 2/4/2021

Date of issue/Date of : 2/4/2021

revision

Date of previous issue : 8/24/2020

Version : 2

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: Not available.

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 2/4/2021 Date of previous issue : 8/24/2020 Version : 2 15/15