

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : SensaMist DARK WOODS  
 CAS-No. : MIXTURE  
 Product code : SM-32-DARK-WOODS

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Vectair Systems Inc  
 2095 Spicer Cove, Covington Way Distribution Centre  
 Memphis TN 38134, USA  
 Toll Free: 877-697-7276 (International) 1 901 373 7818

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC (US & Canada) 1-800-535-5053 | (International) 1-352-323-3500

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) :  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation

Precautionary statements (GHS US) :  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P272 - Contaminated work clothing must not be allowed out of the workplace  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352 - If on skin: Wash with plenty of water  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P321 - Specific treatment (see supplemental first aid instruction on this label)  
 P332+P313 - If skin irritation occurs: Get medical advice/attention.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P363 - Wash contaminated clothing before reuse.  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards which do not result in classification

No additional information available

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
ISO E SUPER	(CAS-No.) 54464-57-2	5 - 10	Skin Irrit. 2, H315 Skin Sens. 1B, H317
FLOROL	(CAS-No.) 63500-71-0	5 - 10	Eye Irrit. 2, H319
BENZYL BENZOATE	(CAS-No.) 120-51-4	5 - 10	Acute Tox. 4 (Oral), H302
CEDRAMBER	(CAS-No.) 19870-74-7	1 - 5	Skin Sens. 1B, H317
METHYL IONONE GAMMA 70	(CAS-No.) 127-51-5	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Linalool	(CAS-No.) 78-70-6	1 - 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
BENZYL SALICYLATE	(CAS-No.) 118-58-1	1 - 5	Eye Irrit. 2, H319 Skin Sens. 1B, H317
DPG - DIPROPYLENE GLYCOL	(CAS-No.) 25265-71-8	1 - 5	Acute Tox. 4 (Inhalation:dust,mist), H332
MAYOL	(CAS-No.) 13828-37-0	1 - 5	Skin Sens. 1B, H317
TONALID	(CAS-No.) 1506-02-1	1 - 5	Acute Tox. 4 (Oral), H302
VANILLIN	(CAS-No.) 121-33-5	1 - 5	Eye Irrit. 2, H319
d-Limonene	(CAS-No.) 5989-27-5	< 0.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

No additional information available

### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### FLOROL (63500-71-0)

Not applicable

##### MAYOL (13828-37-0)

Not applicable

##### BENZYL SALICYLATE (118-58-1)

Not applicable

##### BENZYL BENZOATE (120-51-4)

Not applicable

##### CEDRAMBER (19870-74-7)

Not applicable

##### ISO E SUPER (54464-57-2)

Not applicable

##### Linalool (78-70-6)

Not applicable

##### METHYL IONONE GAMMA 70 (127-51-5)

Not applicable

##### TONALID (1506-02-1)

Not applicable

##### VANILLIN (121-33-5)

Not applicable

##### d-Limonene (5989-27-5)

Not applicable

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### DPG - DIPROPYLENE GLYCOL (25265-71-8)

Not applicable

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): Colourless to light yellow Colourless Yellow White On exposure to light: yellow White to off-white White to light yellow On exposure to light: discolours
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Floral odour Sweet odour Strong odour Characteristic odour Mild odour Pleasant odour Aromatic odour Almost odourless Phenol odour Fruity odour Peppermint odour Lemon odour Alcohol odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 94.9 (≥ 0) °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

BENZYL SALICYLATE (118-58-1)	
LD50 oral rat	3031 - 3339 mg/kg body weight (EU Method B.1: Acute Toxicity (Oral), Rat, Male/female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (EU Method B.3: Acute toxicity (dermal), 24 h, Rabbit, Male/female, Read-across, Dermal, 14 day(s))
ATE US (oral)	2200 mg/kg body weight

BENZYL BENZOATE (120-51-4)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)
ATE US (oral)	1500 mg/kg body weight
ATE US (dermal)	4000 mg/kg body weight

Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	5610 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 7 day(s))
ATE US (oral)	2790 mg/kg body weight
ATE US (dermal)	5610 mg/kg body weight

TONALID (1506-02-1)	
ATE US (oral)	1000 mg/kg body weight

VANILLIN (121-33-5)	
LD50 oral rat	3300 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3300 mg/kg body weight

d-Limonene (5989-27-5)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Weight of evidence, Dermal)

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### DPG - DIPROPYLENE GLYCOL (25265-71-8)

LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 5010 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	2.34 mg/l (Equivalent or similar to OECD 403, Rat, Male / female, Experimental value, Inhalation)
ATE US (vapors)	2.34 mg/l/4h
ATE US (dust, mist)	2.34 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### d-Limonene (5989-27-5)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

### BENZYL SALICYLATE (118-58-1)

LC50 fish 1	1.03 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1.16 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

### BENZYL BENZOATE (120-51-4)

LC50 fish 1	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

### Linalool (78-70-6)

LC50 fish 1	27.8 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	59 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	156.7 mg/l (DIN 38412-9, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>VANILLIN (121-33-5)</b>	
LC50 fish 1	57 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	36.79 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

<b>d-Limonene (5989-27-5)</b>	
LC50 fish 1	720 µg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	0.36 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

<b>DPG - DIPROPYLENE GLYCOL (25265-71-8)</b>	
LC50 fish 1	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value)
LC50 other aquatic organisms 1	3181 mg/l (Other, 48 h, Xenopus laevis, Fresh water, Experimental value)
EC50 Daphnia 1	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

### 12.2. Persistence and degradability

<b>FLOROL (63500-71-0)</b>	
Persistence and degradability	Biodegradability in water: no data available.

<b>MAYOL (13828-37-0)</b>	
Persistence and degradability	Biodegradability in water: no data available.

<b>BENZYL SALICYLATE (118-58-1)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>BENZYL BENZOATE (120-51-4)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>Linalool (78-70-6)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>VANILLIN (121-33-5)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>d-Limonene (5989-27-5)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	3.29 g O <sub>2</sub> /g substance

<b>DPG - DIPROPYLENE GLYCOL (25265-71-8)</b>	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>FLOROL (63500-71-0)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>MAYOL (13828-37-0)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>BENZYL SALICYLATE (118-58-1)</b>	
BCF fish 1	1170 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Danio rerio, Flow-through system, Fresh water, Read-across, GLP)
Log Pow	4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

<b>BENZYL BENZOATE (120-51-4)</b>	
BCF fish 1	2.286 (BCFBAF v3.00, Pisces, QSAR)
Log Pow	3.97 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Linalool (78-70-6)</b>	
Log Pow	2.84 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>VANILLIN (121-33-5)</b>	
Log Pow	1.17 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>d-Limonene (5989-27-5)</b>	
BCF fish 1	864.8 - 1022 (Pisces, QSAR, Fresh weight)
Log Pow	4.38 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 37 °C)
Bioaccumulative potential	Potential for bioaccumulation ( $4 \geq \text{Log Kow} \leq 5$ ).
<b>DPG - DIPROPYLENE GLYCOL (25265-71-8)</b>	
Log Pow	-0.462 (Test data, Equivalent or similar to OECD 107, 21.7 °C)
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

<b>FLOROL (63500-71-0)</b>	
Ecology - soil	No (test)data on mobility of the substance available.
<b>BENZYL SALICYLATE (118-58-1)</b>	
Surface tension	69 mN/m (20 °C, 0.004 g/l, EU Method A.5: Surface tension)
Log Koc	3.75 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
<b>BENZYL BENZOATE (120-51-4)</b>	
Surface tension	0.027 N/m (210 °C)
Log Koc	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
<b>Linalool (78-70-6)</b>	
Surface tension	8.3 mN/m (20 °C, ISO 9101: Surface active agents - Determination of interfacial tension)
Ecology - soil	No (test)data on mobility of the substance available.
<b>VANILLIN (121-33-5)</b>	
Log Koc	3.438 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.
<b>d-Limonene (5989-27-5)</b>	
Ecology - soil	Adsorbs into the soil.
<b>DPG - DIPROPYLENE GLYCOL (25265-71-8)</b>	
Surface tension	71.4 mN/m (22 °C, 1.01 g/l)
Log Koc	0.78 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated

#### Transportation of Dangerous Goods

Not applicable

#### Transport by sea

Not regulated

#### Air transport

Not regulated

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### FLOROL (63500-71-0)

EPA TSCA Regulatory Flag

PMN - PMN - indicates a commenced PMN substance.

#### 15.2. International regulations

##### CANADA

#### FLOROL (63500-71-0)

Listed on the Canadian DSL (Domestic Substances List)

#### MAYOL (13828-37-0)

Listed on the Canadian DSL (Domestic Substances List)

#### BENZYL SALICYLATE (118-58-1)

Listed on the Canadian DSL (Domestic Substances List)

#### BENZYL BENZOATE (120-51-4)

Listed on the Canadian DSL (Domestic Substances List)

#### CEDRAMBER (19870-74-7)

Listed on the Canadian DSL (Domestic Substances List)

#### ISO E SUPER (54464-57-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Linalool (78-70-6)

Listed on the Canadian DSL (Domestic Substances List)

#### METHYL IONONE GAMMA 70 (127-51-5)

Listed on the Canadian DSL (Domestic Substances List)

#### TONALID (1506-02-1)

Listed on the Canadian DSL (Domestic Substances List)

# DARK WOODS TMM MOD VISCOSITY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### VANILLIN (121-33-5)

Listed on the Canadian DSL (Domestic Substances List)

### d-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

### DPG - DIPROPYLENE GLYCOL (25265-71-8)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

No additional information available

### 15.3. US State regulations

#### WARNING:

This product can expose you to Myrcene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*