TMS 2965

MATERIAL SAFETY DATA SHEET

MSDS Number:

332500TMCAFB

1. PRODUCT AND COMPANY IDENTIFICATION

TIME MIST PREMIUM AIR FRESHENER WITH ODOR COUNTERACTANT - ALL FRAGRANCES AND SIZES (30% VOC) Product Name:

Waterbury Companies, Inc.

24-Hour Emergency Contact: 800-424-9300 or 703-527-3887

P.O. Box 640 Independence, LA 70443

(CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components greater than 1.0% (0.1% if carcinogen or suspected carcinogen)

Component	CAS#	OSHAPEL	ACGIH TLV	Other Limits	% bywt.
Acetone	67-64-1	1000 ppm	750 ppm	750 ppm ACGIH STEL	35-45
C8-C9 Isoparaffinic Hydrocarbons	64741-66-8	N.E.	N.E.	400ppm (Exxon)	<5
Diethylene Glycol Monoethyl Ether	111-90-0	N.E.	N.E.	N.E.	20-30
Perfume Oils-Supplier Trade Secret	N/A	N.E.	N.E.	N.E.	5-15
Propane	74-98-6	1000 ppm	1000 ppm	1000 ppm TWA	25-35

3. HAZARDS IDENTIFICATION

Caution! Flammable!

Manufactured by:

Contents under pressure, do not expose to fire or extreme heat. Keep out of reach of children.

Read label. Use caution when installing; product contains an eye irritant. This product is designed for use in the Automatic Aerosol Dispenser. One unit per 6,000 cubic feet should be considered as an average need. Keep in mind that factors such as air flow, size of space, humidity, and room temperature all affect odor control. Do not allow spray to contact plastic, painted, or varnished surfaces.

Potential Health Effects:

Routes of Entry:

Inhalation: Yes

Inglestion: Yes

Health Hazards:

Acetone is irritating and may possibly cause injury to the eyes if not removed promptly. Acetone may have effects on the liver and kidney.

Humans with liver or kidney disease may be at increased risks due to this potential effect.

Signs/symptoms of

overexposure:

High vapor concentrations may cause upper respiratory tract irritation, narcosis (sleepiness, dizziness, etc.), and eye irritation. Prolonged

skin contact may cause mild to moderate local redness and swelling. Contact with eyes may cause severe irritation, experienced as discomfort or pain, excessive blinking and tear production, with marked excess redness and swelling of the conjunctiva. Corneal injury may

OCCUE

Medical conditions aggravated by

Skin contact may aggravate an existing dermatitis.

exposure:

NFPA Hazard Ratings

Fire:

4 Health:

1 Reactivity:

n

NFPA 704 Ratings are subject to interpretation and are only intended for general identification of the level of the specific hazard. All information must be considered for proper safe handling of the material.

4. FIRST AID MEASURES

IF IN EYES: Immediately flush with large amounts of water for at least 15 minutes. Do not remove contact lenses; obtain medical attention immediately. IF ON SKIN OR CLOTHING: Remove contaminated clothing and wash before reuse. Wash affected areas of skin with soap and water for 15-20 minutes. Consult physician if irritation persists. IF INHALED: If large concentrations are inhaled, immediately move to freshair. Keep person calm. If not breathing, give artificial respiration and contact emergency medical personnel. If labored breathing, give oxygen. IF SWALLOWED: Call a physician or Poison Control Center immediately. Do not induce vomiting unless directed by medical personnel. Vomiting may cause aspiration pneumonia hazard. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Extinguishing Media:

CO2, dry chemical or foam

Fire Fighting Procedures:

Self contained air supply suggested. Keep containers cool to avoid bursting.

Unusual Fire and Explosion Hazards:

Exposure to temperatures above 120 deg.F may cause bursting.

6. ACCIDENTAL RELEASE MEASURES

If container is ruptured or begins to leak, place in a well-ventilated area free of spark and ignition sources. Any remaining liquid should be collected with absorbent media. Dispose of unusable concentrate and absorbent media in accordance with Local, State and Federal regulations.

7. HANDLING AND STORAGE

Do not contaminate water, food or feed by storage or disposal. Store in a cool, dry area away from heat or open flame. Exposure to temperatures above 120 deg.F. may cause bursting. Do not install directly over any food handling or dispensing area.

NFPA 30B Aerosol Classification:

Level 3 Aerosol

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Gloves:

Respiratory Protection:

Not required - avoid contact with skin.

Eye Protection:

Safety glasses recommended when installing new container to avoid possible contact with eyes.

Not required - avoid breathing spray.

Ventilation:

Local: Not required.

Mechanical: Not required.

Page 1 of 4

Revision Date: 12/17/2009

Date Printed: 12/18/2009

MATERIAL SAFETY DATA SHEET

Other protective equipment:

N/A

Follow label instructions. Protective Work/Hygiene Practices:

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (H2O=1):

0.73

Flashpoint: Not applicable

LEL: N/A

Vapor Pressure (mmHg):

4,395

Boiling Point: N/A Melting Point:

UEL: N/A

MSDS Number: 332500TMCAFB

N/A

Solubility: Appreciable

Appearance/Odor:

Dry spritz with various characteristic fragrances.

10. STABILITY AND REACTIVITY

Conditions to Avoid:

Heat, sparks, and open flame.

Incompatible Materials:

Oxidizing materials, alkalis, acids, chlorinated compounds.

Hazardous Decomposition By-products:

May liberate Carbon monoxide, and carbon dioxide.

Hazardous Polymerization Conditions:

None known.

11. TOXICOLOGICAL INFORMATION

This product contains no chemicals that are listed on the NTP, IARC, or OSHA carcinogen lists. Any further information on the toxicology of the material can be obtained by contacting the manufacturer.

12. ECOLOGICAL INFORMATION

Please call the manufacturer for questions concerning the ecological effects of this product and it's constituents.

13. DISPOSAL CONSIDERATIONS

Empty the can by using the product according to the label. DO NOT PUNCTURE OR INCINERATE! "Empty" cans may contain residue. Avoid exposure to heat, flame, sparks, and other sources of ignition. IF EMPTY: Place in trash or offer for recycling if available. IF PARTLY FILLED: Call your local solid waste agency or 1-800-CLEANUP for disposal instructions.

14	TOAL	ISPOR"	TIMEC	SM A	TIM

14.110.00.0	Status	Shipping Name	Class	ID Number	Pack Grp
DOT (USA):	Regulated	Consumer Commodity (per 49CFR173.306)	ORM-D	N/A	N/A
IATA (Air):	Regulated	Consumer Commodity	9	ID8000	N/A
IMDG (Vessel):	Regulated	Aerosols	2	UN1950	N/A

National Motor Freight Classification and LTL Class:

57100 Sub 3 Class 60

15. REGULATORY INFORMATION

SARA Title III Section 312:

When completing Tier II reports, the following information should be used.

Note: See state and local regulations for specifics on reporting requirements for your facility.

This product should be described as:

PURE: N MIXTURE: Y

CAS/Category

LIQUID: Y GAS:

Physical Hazards:

FIRE: Y

PRESSURE: Y REACTIVITY: N Health Hazards:

IMMEDIATE: Y

DELAYED: Y

SARA Title III Section 313: Chemical

Toxic chemical components subject to the reporting requirements of EPCRA and 40CFR372

Gly col Ethers

Percent

25.00

16, OTHER INFORMATION

Product Sales Information:

800-845-3495

MSDS Information:

985-878-6751

Revision Notes:

Review of MSDS

N/A = Not Applicable

N.E. = Not Established

(Also covers 33- 2960, 4700, & 5300 series)

MSDS Prepared by: T.Faust

This Information is provided in good faith, but no warranty, expressed or implied, is made. The manufacturer believes that it is accurate and to the best of its knowledge, and relates only to the specific material designated herein.