

WCW031C

MATERIAL SAFETY DATA SHEET

MSDS Number 332500TM

1. PRODUCT AND COMPANY IDENTIFICATION**Product Name:** TIME MIST AIR FRESHENER WITH ODOR COUNTERACTANT - ALL FRAGRANCES AND SIZES (30% VOC COMPLIANT)**Manufactured by:** Waterbury Companies, Inc.
P.O. Box 640
Independence, LA 70443**24-Hour Emergency Contact:**
800-424-9300 or 703-527-3887
(CHEMTREC)**2. COMPOSITION/INFORMATION ON INGREDIENTS***Hazardous components greater than 1.0% (0.1% if carcinogen or suspected carcinogen)*

Component	CAS#	OSHA PEL	ACGIH TLV	Other Limits	% by wt.
Acetone	67-64-1	1000 ppm	750 ppm	750 ppm ACGIH STEL	35-45
C8-C9 Isoparaffinic Hydrocarbons	64741-66-8	N.E.	N.E.	400ppm (Exxon)	<5
Diethylene Glycol Monoethyl Ether	111-90-0	N.E.	N.E.	N.E.	25-35
Perfume Oils-Supplier Trade Secret	N/A	N.E.	N.E.	N.E.	5-15
Propane	74-98-6	1000 ppm	1000 ppm	1000 ppm TWA	25-35

3. HAZARDS IDENTIFICATION**Warning!** Flammable!

Contents under pressure, do not expose to fire or extreme heat.

Read label. Use caution when installing; product contains an eye irritant. This product is designed for use in the Automatic Aerosol Dispenser. One unit per 6,000 cubic feet should be considered as an average need. Keep in mind that factors such as air flow, size of space, humidity, and room temperature all affect odor control. Do not allow spray to contact plastic, painted, or varnished surfaces.

Potential Health Effects:**Routes of Entry:** Inhalation: Yes Ingestion: Yes Skin: Yes**Health Hazards:** Acetone is irritating and possibly injurious to the eyes if not removed promptly. Acetone may increase the toxicity to the liver and kidney of chemicals such as ethanol, 1,2-dichloroethane, and chloroform. Humans with liver or kidney disease may be at increased risks due to this potential effect.**Signs/symptoms of overexposure:** High vapor concentrations may cause upper respiratory tract irritation, narcosis (sleepiness, dizziness, etc.), and eye irritation. Prolonged skin contact may cause mild to moderate local redness and swelling. Contact with eyes may cause severe irritation, experienced as discomfort or pain, excessive blinking and tear production, with marked excess redness and swelling of the conjunctiva. Corneal injury may occur.**Medical conditions aggravated by exposure:** Skin contact may aggravate an existing dermatitis.**NFPA Hazard Ratings** Fire: 4 Health: 1 Reactivity: 0*NFPA 704 Ratings are subject to interpretation and are only intended for general identification of the level of the specific hazard. All information must be considered for proper safe handling of the material.***4. FIRST AID MEASURES**

IF IN EYES: Immediately flush with large amounts of water for at least 15 minutes. Do not remove contact lenses; obtain medical attention immediately. IF ON SKIN OR CLOTHING: Remove contaminated clothing and wash before reuse. Wash affected areas of skin with soap and water for 15-20 minutes. Consult physician if irritation persists. IF INHALED: If large concentrations are inhaled, immediately move to fresh air. Keep person calm. If not breathing, give artificial respiration and contact emergency medical personnel. If labored breathing, give oxygen. IF SWALLOWED: Call a physician or Poison Control Center immediately. Do not induce vomiting unless directed by medical personnel. Vomiting may cause aspiration pneumonia hazard. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES**Extinguishing Media:** CO2, dry chemical or foam**Fire Fighting Procedures:** Self contained air supply suggested. Keep containers cool to avoid bursting.**Unusual Fire and Explosion Hazards:** Exposure to temperatures above 120 deg.F may cause bursting.**6. ACCIDENTAL RELEASE MEASURES**

If container is ruptured or begins to leak, place in a well-ventilated area free of spark and ignition sources. Any remaining liquid should be collected with absorbent media. Dispose of unusable concentrate and absorbent media in accordance with Local, State and Federal regulations.

7. HANDLING AND STORAGE

Do not contaminate water, food or feed by storage or disposal. Store in a cool, dry area away from heat or open flame. Exposure to temperatures above 120 deg.F. may cause bursting. Do not install directly over any food handling or dispensing area.

NFPA 30B Aerosol Classification: Level 3 Aerosol**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Protective Gloves:** Not required - avoid contact with skin.**Eye Protection:** Safety glasses recommended when installing new container to avoid possible contact with eyes.

MATERIAL SAFETY DATA SHEET

MSDS Number 332500TM

1. PRODUCT AND COMPANY IDENTIFICATION**Product Name:** TIME MIST AIR FRESHENER WITH ODOR COUNTERACTANT - ALL FRAGRANCES AND SIZES (30% VOC COMPLIANT)**Manufactured by:** Waterbury Companies, Inc.
P.O. Box 640
Independence, LA 70443**24-Hour Emergency Contact:**
800-424-9300 or 703-527-3887
(CHEMTREC)**2. COMPOSITION/INFORMATION ON INGREDIENTS***Hazardous components greater than 1.0% (0.1% if carcinogen or suspected carcinogen)*

Component	CAS#	OSHA PEL	ACGIH TLV	Other Limits	% by wt.
Acetone	67-64-1	1000 ppm	750 ppm	750 ppm ACGIH STEL	35-45
C8-C9 Isoparaffinic Hydrocarbons	64741-66-8	N.E.	N.E.	400ppm (Exxon)	<5
Diethylene Glycol Monoethyl Ether	111-90-0	N.E.	N.E.	N.E.	25-35
Perfume Oils-Supplier Trade Secret	N/A	N.E.	N.E.	N.E.	5-15
Propane	74-98-6	1000 ppm	1000 ppm	1000 ppm TWA	25-35

3. HAZARDS IDENTIFICATION**Warning!** Flammable!

Contents under pressure, do not expose to fire or extreme heat.

Read label. Use caution when installing; product contains an eye irritant. This product is designed for use in the Automatic Aerosol Dispenser. One unit per 6,000 cubic feet should be considered as an average need. Keep in mind that factors such as air flow, size of space, humidity, and room temperature all affect odor control. Do not allow spray to contact plastic, painted, or varnished surfaces.

Potential Health Effects:**Routes of Entry:** Inhalation: Yes Ingestion: Yes Skin: Yes**Health Hazards:** Acetone is irritating and possibly injurious to the eyes if not removed promptly. Acetone may increase the toxicity to the liver and kidney of chemicals such as ethanol, 1,2-dichloroethane, and chloroform. Humans with liver or kidney disease may be at increased risks due to this potential effect.**Signs/symptoms of overexposure:** High vapor concentrations may cause upper respiratory tract irritation, narcosis (sleepiness, dizziness, etc.), and eye irritation. Prolonged skin contact may cause mild to moderate local redness and swelling. Contact with eyes may cause severe irritation, experienced as discomfort or pain, excessive blinking and tear production, with marked excess redness and swelling of the conjunctiva. Corneal injury may occur.**Medical conditions aggravated by exposure:** Skin contact may aggravate an existing dermatitis.**NFPA Hazard Ratings** Fire: 4 Health: 1 Reactivity: 0*NFPA 704 Ratings are subject to interpretation and are only intended for general identification of the level of the specific hazard. All information must be considered for proper safe handling of the material.***4. FIRST AID MEASURES**

IF IN EYES: Immediately flush with large amounts of water for at least 15 minutes. Do not remove contact lenses; obtain medical attention immediately. IF ON SKIN OR CLOTHING: Remove contaminated clothing and wash before reuse. Wash affected areas of skin with soap and water for 15-20 minutes. Consult physician if irritation persists. IF INHALED: If large concentrations are inhaled, immediately move to fresh air. Keep person calm. If not breathing, give artificial respiration and contact emergency medical personnel. If labored breathing, give oxygen. IF SWALLOWED: Call a physician or Poison Control Center immediately. Do not induce vomiting unless directed by medical personnel. Vomiting may cause aspiration pneumonia hazard. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES**Extinguishing Media:** CO2, dry chemical or foam**Fire Fighting Procedures:** Self contained air supply suggested. Keep containers cool to avoid bursting.**Unusual Fire and Explosion Hazards:** Exposure to temperatures above 120 deg.F may cause bursting.**6. ACCIDENTAL RELEASE MEASURES**

If container is ruptured or begins to leak, place in a well-ventilated area free of spark and ignition sources. Any remaining liquid should be collected with absorbent media. Dispose of unusable concentrate and absorbent media in accordance with Local, State and Federal regulations.

7. HANDLING AND STORAGE

Do not contaminate water, food or feed by storage or disposal. Store in a cool, dry area away from heat or open flame. Exposure to temperatures above 120 deg.F. may cause bursting. Do not install directly over any food handling or dispensing area.

NFPA 308 Aerosol Classification: Level 3 Aerosol**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Protective Gloves:** Not required - avoid contact with skin.**Eye Protection:** Safety glasses recommended when installing new container to avoid possible contact with eyes.