

Wood Care: Ultra Low Odor Waterbased Sealer

| HMIS NFP | | NFPA | Personal protective equipment | |
|-------------------------------|---|------|-------------------------------|--|
| Health | 1 | 1 | None / Aucune / Ninguno | |
| Flammability | 0 | 0 | ar in arm in grant | |
| Physical Hazard / Instability | 0 | 0 | | |

Version Number: 1 Preparation date: 2012-02-01

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Wood Care: Ultra Low Odor Waterbased Sealer

 MSDS #:
 MS0300348

 Product Code:
 5142219

Recommended use: Industrial/Institutional. Floor care.

Manufacturer, importer, supplier:Canadian HeadquartersUS HeadquartersDiversey, Inc. - CanadaDiversey, Inc.2401 Bristol Circle8310 16th St.Oakville, Ontario L6H 6P1Sturtevant, Wisconsin 53177-1964Phone: 1-800-668-3131

Phone: 1-888-352-2249

MSDS Internet Address: www.diversey.com

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION. MAY BE MILDLY IRRITATING TO EYES. MAY BE MILDLY IRRITATING TO SKIN.

Principal routes of exposure:Eye contact. Skin contact. Inhalation.Eye contact:May be mildly irritating to eyes.Skin contact:May be mildly irritating to skin.

Inhalation: None Ingestion: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient(s) | CAS# | Weight % | LD50 Oral - Rat (mg/kg) | LD50 Dermal - Rabbit | LC50 Inhalation - Rat |
|---------------------------------|------------|------------|----------------------------|-------------------------|--------------------------|
| Diisobutyl adipate | 141-04-8 | 0.1 - 1.5% | 5676 | Not available | Not available |
| Dipropylene glycol methyl ether | 34590-94-8 | 1 - 5% | 5230 | 9500 mg/kg | Not available |

4. FIRST AID MEASURES

Eye contact: Flush immediately with plenty of water. If irritation develops, get medical attention. **Skin contact:** Flush immediately with plenty of water. If irritation develops, get medical attention.

Inhalation: No specific first aid measures are required. Ingestion: No specific first aid measures are required.

Aggravated Medical Conditions: None known

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards: Not applicable Unusual hazards: None known

Specific methods: No special methods required

Wood Care: Ultra Low Odor Waterbased Sealer

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment

Environmental precautions Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use

and clean-up methods: a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection:No special requirements under normal use conditions.Hand protection:No special requirements under normal use conditionsSkin and body protection:No special requirements under normal use conditions.Respiratory protection:No special requirements under normal use conditions.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

| Ingredient(s) | CAS# | ACGIH | OSHA | Mexico |
|---------------------------------|------------|----------------|-------------------------------------|--------------------------------------|
| Dipropylene glycol methyl ether | 34590-94-8 | 150 ppm (STEL) | Skin | 150 ppm (STEL) 900 mg/m ³ |
| | | 100 ppm (TWA) | 100 ppm (TWA) 600 mg/m ³ | (STEL) |
| | | | (TWA) | 100 ppm (TWA) 60 mg/m ³ |
| | | | | (TWA) |

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: LiquidBulk density: No information availableAppearance: LiquidEvaporation Rate No information available

Specific gravity: 1.04

Vapor density: No information available

Odor: Sweet

Odor: Sweet

Boiling point/range: Not determined Melting point/range: Not determined

Decomposition temperature: Not determined **Autoignition temperature:** No information available

Solubility: Partially SolubleDensity: 8.67 lbs/gal 1.04 Kg/LSolubility in other solvents: No information availableFlash point: >200 °F >93.4 °CPartition coefficient (n-octanol/water): No information availableViscosity:No information availableElemental Phosphorus: 0 % by wt.VOC: 100 g/L (40 CFR §59.400)

pH: 7.8 **VOC:** 100 g/L (40 CFR §59.400)

Explosion limits: - upper: Not determined - lower: Not determined

10. STABILITY AND REACTIVITY

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur

Hazardous decomposition products: None reasonably foreseeable.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Oral LD50 estimated to be greater than 5000 mg/kg; Dermal LD50 estimated to be > 2000 mg/kg

Component Information: See Section 3

Chronic toxicity: None known

Wood Care: Ultra Low Odor Waterbased Sealer

Specific effects

 Carcinogenic effects:
 None known

 Mutagenic effects:
 None known

 Reproductive toxicity:
 None known

 Target organ effects:
 None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

RIGHT TO KNOW (RTK)

| Ingredient(s) | CAS# | MARTK: | NJRTK: | PARTK: | RIRTK: |
|---------------------------------|------------|--------|--------|--------|--------|
| Diisobutyl adipate | 141-04-8 | = | • | • | - |
| Dipropylene glycol methyl ether | 34590-94-8 | X | X | X | X |
| Proprietary | TS* | = | = | = | = |
| Water | 7732-18-5 | - | • | - | - |

CERCLA/ SARA

SARA 311/312 Hazard Categories

Immediate: Delayed: Fire: Reactivity: Sudden Release of Pressure: -

Canada

WHMIS hazard class: Non-controlled

16. OTHER INFORMATION

Reason for revision: Not applicable Prepared by: NAPRAC

Wood Care: Ultra Low Odor Waterbased Sealer

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.